

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil C
P.O. Box 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT --" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well: ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator

TEXACO EXPLORATION & PRODUCTION INC.

3. Address and Telephone No.

P.O. Box 2100, Denver Colorado 80201

(303)793-4851

9. API Well No.

30-025-34010

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter B 330 Feet From The NORTH Line and 1650 Feet From The

EAST Line Section 35 Township 24-S Range 37-E

10. Field and Pool, Exploratory Area

JUSTIS BLINEBRY / JUSTIS TUBB DRINKARD

11. County or Parish, State

LEA, NM

12. Check Appropriate Box(s) To Indicate Nature of Notice, Report, or Other Data

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION


- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ OTHER: SPUD, SURF, PROD CSG.

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- NABORS RIG #403 SPUD 11 INCH HOLE @ 7:00 PM 07-06-97. DRILLED TO 938'. TD @ 5:15 AM CST 07-07-97.
- RAN 34 JOINTS OF 8 5/8 INCH, 24#, WC-50, STC CASING SET @ 1476'. RAN 10 CENTRALIZERS.
- DOWELL CEMENTED WITH 325 SACKS CLASS C W/ 4% GEL, 2% CACL2 (13.5 PPG, 1.74 CF/S). F/B 200 SACKS CLASS C W/ 2% CACL2 (14.8 PPG, 1.34 CF/S). PLUG DOWN @ 11:45 AM 07-07-97. CIRCULATED 150 SACKS.
- NU BOP & TESTED TO 1500#. TESTED CASING TO 1500# FOR 30 MINUTES FROM 10:15 PM TO 10:45 PM 07-07-97.
- WOC TIME 10-1/2 HOURS FROM 11:45 AM 07-07-97 TO 10:15 PM 07-07-97.
- DRILLING 7 7/8 INCH HOLE.
- DRILLED 7 7/8 INCH HOLE TO 6458'. TD @ 3:15 PM 07-15-97.
- MIRU SCHLUMBERGER AND LOG. LOGGERS TO @ 6460'.
- RAN 49 JOINTS OF 4 1/2 INCH, 11.6#, L-80 AND 103 JOINTS OF 4 1/2 INCH, 11.6#, K-55, LTC CASING SET @ 6458'.
- DOWELL CEMENTED: - 700 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 700 SACKS 50/50 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (14.2 PPG, 1.35 CF/S). PLUG DOWN @ 1:30 PM 07-16-97.
- ND. RELEASE RIG @ 5:30 PM 07-16-97.
- PREP TO COMPLETE.



14. I hereby certify that the foregoing is true and correct

SIGNATURE C. P. Basham SRH TITLE Eng. Assistant.

DATE 7/18/97

TYPE OR PRINT NAME Sheilla D. Reed-High

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY: TITLE DATE

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.