SUND	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT RY NOTICES AND REPORTS ON WI	N.M. Oil Cons. P.C. 31960 Hobbs, NM 8824 ELLS	5. Lease Designation and Serial No. NM 14218
Do not use this form for Use "AF	PPLICATION FOR PERMIT" for such pro	posals	6. If Indian, Alottee or Tribe Name
	SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
Type of Well: OIL WELL			8. Well Name and Number FRISTOE, C.C. NCT-2
Name of Operator TEX/	ACO EXPLORATION & PRODUCTION INC	C	24
Address and Telephone No. P.O.	. Box 2100, Denver Colorado 80201	(303)793-4851	9, API Well No.
Location of Well (Footage, Sec., T.,	R., M., or Survey Description) Feet From The NORTH Line and 1048	Feet From The	10. Field and Pool, Exploratory Area BLINEBRY, TUBB, DRINKARD
Jnit Letter H 1491		Range 37-E	11. County or Parish, State LEA , NM
2. Check A TYPE OF SUBMISSION	Appropriate Box(s) To Indicate I	Nature of Notice, R	
 Notice of Intent Subsequent Report Final Abandonment Notice 	B Recomp Pluggin Casing Altering OTHER	g Back Repair Casing	New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection SG Dispose Water
directionally drilled, give subsurface 1. DRILLED 7 7/8 INCH HOL 2. RAN 122 JOINTS OF 4 1/2 3. DOWELL CEMENTED: 7/200 SACKS POZ CLASS	CE IOCANONS AND MILESUIEU AND UNE VENUEL OPA- 2 INCH, 11.6#, K55 AND 20 JOINTS OF 4 00 SACKS 35/65 POZ CLASS H W/ 6% GI H W/6% GEL, 5% SALT, 1/4# FLOCELE (0 PLUGGED, FLOAT HELD.	1/2 INCH, 11.6#,L-80, LT	C CASING SET @ 6450'.
directionally drilled, give subsurface 1. DRILLED 7 7/8 INCH HOL 2. RAN 122 JOINTS OF 4 1/2 3. DOWELL CEMENTED: 7/2 700 SACKS POZ CLASS TO SURFACE. BUMPED 4. ND. RELEASE RIG @ 2:1	CE IOCANONS AND MILESUIEU AND UNE VENUEL OPA- 2 INCH, 11.6#, K55 AND 20 JOINTS OF 4 00 SACKS 35/65 POZ CLASS H W/ 6% GI H W/6% GEL, 5% SALT, 1/4# FLOCELE (0 PLUGGED, FLOAT HELD.	1/2 INCH, 11.6#,L-80, LT	completion or Recompletion Report and Log Form.) Ig estimated date of starting any proposed work. If well is ertinent to this work.)*. IC CASING SET @ 6450'. IS E 5 (12.4 PPG, 2.10 CF/S) F/B
directionally drilled, give subsurface 1. DRILLED 7 7/8 INCH HOL 2. RAN 122 JOINTS OF 4 1/2 3. DOWELL CEMENTED: 7/2 700 SACKS POZ CLASS TO SURFACE. BUMPED 4. ND. RELEASE RIG @ 2:1	CE IOCANONS AND MILESUIEU AND UNE VENUEL OPA- 2 INCH, 11.6#, K55 AND 20 JOINTS OF 4 00 SACKS 35/65 POZ CLASS H W/ 6% GI H W/6% GEL, 5% SALT, 1/4# FLOCELE (0 PLUGGED, FLOAT HELD.	1/2 INCH, 11.6#,L-80, LT	completion or Recompletion Report and Log Form.) Ig estimated date of starting any proposed work. If well is ertinent to this work.)*. IC CASING SET @ 6450'. IS E 5 (12.4 PPG, 2.10 CF/S) F/B
directionally drilled, give subsurfact 1. DRILLED 7 7/8 INCH HOL 2. RAN 122 JOINTS OF 4 1/2 3. DOWELL CEMENTED: 7/2 700 SACKS POZ CLASS TO SURFACE. BUMPED 4. ND. RELEASE RIG @ 2:1 5. PREP TO COMPLETE. 14. Lhereby certify that the foregoing is true and	ce locations and measured and tide vehicle oper- LE TO 6350'. 2 INCH, 11.6#, K55 AND 20 JOINTS OF 4 00 SACKS 35/65 POZ CLASS H W/ 6% GI H W/6% GEL, 5% SALT, 1/4# FLOCELE (0 PLUGGED, FLOAT HELD. 15 PM 02-24-98.	1/2 INCH, 11.6#,L-80, LT EL, 5% SALT, 1/4# FLOC 14.2 PPG, 1.33 CF/S). FI	Completion or Recompletion Report and Log Form.) Ig estimated date of starting any proposed work. If well is ertinent to this work.)*. IC CASING SET @ 6450'. ELE (12.4 PPG, 2.10 CF/S). F/B ULL RETURNS THROUGHOUT. NO CEMENT

Title 18 U.S.C. Section 1001, makes it a crime for any representations as to any matter within its jurisdiction.

.

..

