

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

1625 N. French Drive
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Enron Oil & Gas Company

3. Address and Telephone No.

P.O. Box 2267 Midland, TX 79702

915/686-3600

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1980' FWL
Sec.11-T25S-R33E

5. Lease Designation and Serial No.

NM-30400

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Triste Draw "11" 1
Federal

9. API Well No.

30-025-34635

10. Field and Pool, or exploratory Area

Vaca Draw (Wolfcamp)

11. County or Parish, State

Lea County NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☒ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

07/17/99-RU Halliburton and cement.

Plug 1-12975' to 12775'(35sx-Class "H" + 1/10% HR-7, 15.6 ppg, 1.18 ft3/sx)

Plug 2-9291' to 9141'(26sx-Class "H" + 1/10% HR-7, 15.6 ppg, 1.18 ft3/sx)

Plug 3-7000' to 9850'(26sx-Class "H" Neat, 15.6 ppg, 1.18 ft3/sx)

RIH with 5-1/2" casing cutter. Cut casing at 5024' and pull 5-1/2" casing out of hole.

Plug 4-5074' to 4974'(45sx-Class "H" Neat, 15.6 ppg, 1.18 ft3/sx)

Plug 5-4964' to 4834'(61sx-Premium Plus Class "C" + 2% CaCl, 14.8 ppg, 1.32 ft3/sx)

RIH and tagged top of cement plug at 4834'.

Plug 6-2600' to 2500'(26sx-Premium Plus Class "C" + 2% CaCl, 14.8 ppg, 1.32 ft3/sx)

Plug 7-733' to 633'(26sx-Premium Plus Class "C" Neat, 14.8 ppg, 1.32 ft3/sx)

Plug 8-60' to surface (20sx-Premium Plus Class "C" + 2% CaCl, 14.8 ppg, 1.32 ft3/sx)

Clean cellar, cut-off wellhead and install dry hole marker. Clean pits and restore location.

14. I hereby certify that the foregoing is true and correct

Signed

Mike Francis

Title

Mike Francis, Agent

Date


07/19/99

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:



Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

VC GWW

JP