

## DRILLING PROGRAM

EOG RESOURCES, INC.  
Hallwood "12" Federal No. 11

LEA COUNTY, NM

- 7" 2<sup>nd</sup> Intermediate: Cement with 800 sx Premium + 3% Econolite + 5 lb/sk Salt (3%) + .25 lb/sk Flocele + 250 sx Premium 50/50 Pozmix 'A' + 2% Halliburton-Gel First 2% + 0.5% Halad-322 + 0.2% HR-5.
- 4-1/2" Production: 520 sx Premium + 0.3% Halad-344 + .3% Halad-413 + .3% Super CBL + .3% SCR-100. This cement slurry is designed to bring TOC to 11,800'.

### 5. MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL:

The blowout preventer equipment (BOP) shown in Exhibit #1 will consist of a double ram-type (5000 psi WP) preventer and an annular preventer (5000 psi WP). Units will be hydraulically operated and the ram-type will be equipped with blind rams on top and drill pipe rams on bottom. All will be installed on the 11 3/4" surface casing and used continuously until TD is reached. All BOP's and accessory equipment will be tested to 600 psi before drilling out of surface casing. Before drilling out of intermediate casing, the ram-type BOP and accessory equipment will be tested to 5000 psi and the annular to 70% of rated working pressure (3500 psi).

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. A 2" kill line and 4" choke line will be included in the drilling spool located below the ram-type BOP. Other accessories to the BOP equipment will include a kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold with 5000 psi WP rating.

### 6. TYPES AND CHARACTERISTICS OF THE PROPOSED MUD SYSTEM:

The well will be drilled to TD with a combination of brine, cut brine, and polymer/KCL mud system. The applicable depths and properties of this system are as follows:

<u>Depth</u>	<u>Type</u>	<u>Wt (ppg)</u>	<u>Viscosity (sec)</u>	<u>Waterloss (cc)</u>
0-650'	Fresh Water (spud)	8.5	40-45	N.C.
650'-5000'	Brine Water	10.0	30	N.C.
5000'- 12700'	Cut Brine & Polymer/KCL	8.8-9.2	28	N.C.
12700'-17800'		8.33	28	N.C.