Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division 1625 N. Fr. ch Dr. Hobbs, NM 88240

FORM APPROVED

Sudget Bureau No. 1004-0135

Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT --" for such proposals


5. Lease Designation and Serial No. LC 061873

6. If Indian, Alottee or Tribe Name

	SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation	
Type of Well: W	L GAS ELL WELL OTHER	8. Well Name and Number COTTON DRAW UNIT	
2. Name of Operator	TEXACO EXPLORATION & PRODUCTION INC.	88	
. Address and Telephone No.	205 E. Bender, HOBBS, NM 88240 397-0405	9. API Well No. 30-025-35086	
	ec., T., R., M., or Survey Description) 210 Feet From The SOUTH Line and 1360 Feet From The	10. Field and Pool, Exploaratory Area PADUCA SOUTH, WOLFCAMP	
WEST Line Sec	tion 7 Township 25-S Range 32-E	11. County or Parish, State LEA , NM	
^{2.} Ch	eck Appropriate Box(s) To Indicate Nature of Notice, F	Report, or Other Data	
TYPE OF SUBMISS	ON	TYPE OF ACTION	
Notice of Intent ✓ Subsequent Report Final Abandonment	Atlering Casing	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water	

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*.

8-18-00/9-03-00: RAN 7" CSG, 96 JTS 32# C-95 LT&C 4333.43', 183 JTS 29# C-95 LT&C 8493.55', ECP @ 8481, DV @ 8484. TOTAL SET @ 12817. CMT 1ST STG W/710 SX 50/50 POZ H W/2% GEL, 5% SALT, 1/4# FLOCELE, 14.2 PPG, 1.35 YIELD, FOLLOWED BY 110 SX CL H W/3% GEL, 5% SALT, 1/4# FLOCELE, 15.5 PPG, 1.18 YIELD DISP W/469 BBL WTR. LAND PLUG. SET ECP OPEN DV TOOL. CMT 2ND STG W/530 SX CL H, W/3% GEL, 5% SALT, 1/4# FLOCELE, 11.5 PPG, 2.98 YIELD, FOLLOWED BY 120 SX 50/50 POZ H W/2% GEL. 5% SALT,, 1/4# FLOCELE, 14.2 PPG, 1.35 YIELD, DISPL W/325 BW & LAND PLUG. TOP CMT @ 4585', 235' BELOW 9 5/8" CSG. DRILL 8395-8461. DRILL DV TOOL @ 8461 TO 8464. DRILL FC & CMT TO 12801'... DRILL 12801-12817,12846,12878,12936,12938,12955,12960,12992,13008,13037,13066,13100,13102, TD. TIH W/PLARFORM EXPRESS, BHC.



14. I hereby certify that the foregoing is true and correct SIGNATURE	se Stake	TITLE Engineering Assistant		DATE	9/4/00
TYPE OR PRINT NAME (This space for Federal or State office use)	J. Denise Leake				7=0 L.T L.T
APPROVED 8\(\text{Modifions of APPROVAL IF ANY:} \)	TITLE	tosan statul Elbati 88	DATE	thing,	_200 1