

(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Conservation Division
1625 N. French Dr.
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT --" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well: ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
TEXACO EXPLORATION & PRODUCTION INC.

3. Address and Telephone No. 15 SMITH ROAD, MIDLAND, TX 79705 915-687-737

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Unit Letter I : 2310 Feet From The SOUTH Line and 990 Feet From The

EAST Line Section 26 Township 24-S Range 37-E

Well Designation and Serial No.

NM-14218

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and Number
C.C. FRISTOE "B" FEDERAL NCT-2

27

9. API Well No.
30-025-35589

10. Field and Pool, Exploratory Area
FOWLER ELLENBURGER

11. County or Parish, State
LEA, NM

12. Check Appropriate Box(s) To Indicate Nature of Notice, Report, or Other Data

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ OTHER: COMPLETION

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

11-27-01: MIRU KEY #311. TIH W/208 JTS 2 7/8" TBG. TAG CMT @ 6637. DRLD CMT TO 6780. 11-30-01: TAG CMT @ 6780. DRILL CMT THRU DV TOOL @ 6837. TAG CMT @ 9870. DRILL CMT TO FC @ 9886.
12-02-01: RAN PDC GR/CCL FR 9886-7700. TIED INTO OPEN HOLE LOG. PERF ELLENBURGER 9724-9751. TIH W/TP. PKR, SN, & PROD TBG. RAN 314 JTS 2 7/8" TBG. SET PKR @ 9674. SN @ 9632. 12-04-01: PUMP 1945 GALS 20% NEFE DN TBG W/BYPASS OPEN. CLOSE BYPASS. PUMP REMAINING 554 GALS ACID @ .4 BPM @ 4225 PSI. START DISPLACEMENT. RU SWAB. 12-07-01: REL PKR. 12-08-01: SET RBP @ 9718. DUMP 3' SAND ON RBP. PERF 9687-9706. TIH W/2 7/8" TBG, PKR, SN. 12-11-01: SPOT 50 GALS 20% HCL ACR PERFS 9687-9706. SET PKR @ 9572. PUMP 2000 GALS 20% HCL. ACIDIZED PERFS 9687-9706. SWABBING. RECD 12 BO. 12-15-01: REL PKR. BAIL SAND FR TOP OF RBP @ 9718. 12-16-01: SET RBP @ 9702. REL & LD. PUMU "G" LOCK SET RBP & SET @ 9665.
12-18-01: RUN #1 RIW & DUMP SAND ON TOP OF RBP @ 9655. #2 RIW W/3 4" PORTED PLUG GUNS TO PERF. MISS FIRE. #3 RIW W/3 4" PORTED PLUG GUNS & PERF ELLENBURGER 9610-9634. TIH W/87 STANDS 2 7/8" TBG. 12-19-01: SET PKR @ 9489. TP @ 9557 & SN @ 9458. ACIDIZE W/59.5 BBLS 20% HCL & DISPL TO BTM PERF 57 BBLS 2% KCL WTR. RU SWAB. 12-28-01: SET PKR. PU BAILER & TIH. TAG SAND @ 9660. 12-29-01: TIH W/RETR TOOL. LATCH ONTO PLUG @ 9665. REL. PU MUD JOINT, SN (9762) TBG, & TAC. SET TAC W/16 POINTS TENSION. INSTL FLANGE. W/O ROD DESIGN & PUMPING UNIT.
1-10-02: TIH W/PMP & RDS.
1-11-02: OIN 24 HR OPT. PUMPED 155 BO, 31 BW, & 221 MCF. FINAL REPORT

14. I hereby certify that the foregoing is true and correct.

SIGNATURE J. Denise Leake TITLE Regulatory SpecialistDATE 2/8/02TYPE OR PRINT NAME J. Denise Leake

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ORIGINAL SIGNED BY
PAUL F. KAUTZ
PETROLEUM ENGINEER

DATE

APR 03 2002

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

3
C
S

RECEIVED

2002 FEB 21 AM 8:35

DEPT OF HEALTH
HOSPITALS

100-100000-100000