

# **HYDROGEN SULFIDE DRILLING OPERATIONS PLAN**

## **C. C. FRISTOE "A" FEDERAL NCT-1 WELL NO. 14**

### **TRAINING:**

Every person involved in the wellsite operation will be informed of the characteristics of hydrogen sulfide, its danger, safe procedures to be used when it is encountered, use of detection equipment, use of protective breathing equipment, and first aid procedures for regular rig personnel.

On site training will be provided by ChevronTexaco prior to reaching Order 6 compliance depth. The ChevronTexaco drilling supervisor is responsible for insuring all persons working on location have been provided training.

### **EXHIBIT A**

Topographic map of location and surrounding area.

### **EXHIBIT B**

The wellsite layout contains the following information:

- Drill rig orientation
- Prevailing wind direction
- Location of all briefing areas
- Location of access road
- Location of flare line
- Location of windsocks
- Location of H2S Safety Trailer

### **PROTECTIVE EQUIPMENT:**

4 – 30 minute SCBA's: 2 located at each Briefing Station. An additional SCBA will be located at the Tool Pusher's trailer, if used.

5 – 5 minute escape packs will be located in the Dog House.

Means of communication while using protective equipment will be hand signals.

### **H2S SENSORS:**

H2S sensors will be located at (1) Shale Shaker (2) Rotating Head and (3) Rig floor.