



AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Calbertson & Irwin, Inc.

Box 1071, Midland, Texas

Company or Operator **Dana** Well No. **2** in **NE/4** of Sec. **24** Address **T. 24S**
Lease **36E** N. M. P. M. **Langlie-Mattix** Field, **Lee** County.
Well is **1980** feet south of the North line and **330** feet west of the East line of **Section 24**
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is **Fowler Hair (surface)** Address **Jal, New Mexico**
If Government land the permittee is Address
The Lessee is Address
Drilling commenced **4/18** 19 **50** Drilling was completed **5/4/** 19 **50**
Name of drilling contractor **Oil Well Remedial Service** Address **Odessa, Texas**
Elevation above sea level at top of casing **3310** feet.
The information given is to be kept confidential until **Not confidential** 19.

OIL SANDS OR ZONES

No. 1, from **3015** to **3030** No. 4, from **3205** to **3220**
No. 2, from **3060** to **3070** No. 5, from to
No. 3, from **3085** to **3095** No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	OUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8	28#	8	S.H.	310	T.P.				
5 1/2	14#	8	Sm. 2983		Float				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
11	8 5/8	310'	125	Halliburton		
8	5 1/2	2983'	400	" 2-stage		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from **0** feet to **3230** feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing **May 4** 19 **50**
The production of the first 24 hours was **54** barrels of fluid of which **100** % was oil; **0** % emulsion; **0** % water; and **0** % sediment. Gravity, Be. **37°**
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

OIL WELL REMEDIAL SERVICE, Driller Driller
CONTRACTOR Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **5th** day of **May**, 19 **50**
Sarane Franklin
Notary Public

Midland, Texas **5/5/50**
Name **William B. Irwin**
Position **President**
Representing **Calbertson & Irwin, Inc.**
Company or Operator
Address **Box 1071, Midland, Texas**

My Commission expires **June 1, 1951**

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	30	30	Sand & caliche
30	105	75	Sand & gravel
105	250	145	Sand & shale
250	730	480	Sand & gray shale
730	900	170	Sand shale & sand
900	1170	270	Sand rock
1170	1285	115	Anhydrite
1285	1350	65	Salt
1350	1500	150	Anhydrite, salt & red rock
1500	1580	80	Salt
1580	1630	50	Anhydrite
1630	1810	180	Salt & anhydrite shells
1810	1960	150	Salt
1960	2010	50	Anhydrite
2010	2250	240	Salt
2250	2450	200	Salt & anhydrite
2450	2600	150	Salt
2600	2670	70	Anhydrite
2670	2850	180	Salt
2850	2870	20	Anhydrite
2870	3000	130	Brown lime
3000	3010	10	Anhydrite
3010	3040	30	Lime & sand
3040	3080	40	Lime
3080	3070	10	Sand
3070	3100	30	Lime & sand
3100	3110	10	Lime
3110	3185	75	Lime, shale and little sand
3185	3205	20	Lime
3205	3220	15	Sand
3220	3230	10	Lime

3.2.3230