

DUPLICATE

(Form C-102)
(Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) To Fracture	X

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

July 26, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the **Humble Oil & Refining Company**
(Company or Operator) Well No. **2** in **2** (Unit)
SE 1/4 **SW** 1/4 of Sec. **26**, T. **24-S**, R. **24-E**, NMPM., **Jalisco** Pool
Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Move in workover unit, kill well and pull 2-inch tubing.
2. Run open hole caliper survey; if necessary clean hole to total depth, 3125'.
3. Run 4-inch hydraulic straddle packers, set approximately 30 feet apart, on 3" or 3 1/2" ID tubing and set bottom packer at 3125 feet.
4. Test zone; break down formation with lease crude, treat 3125-3125 with 10,000 gallons refined oil (1/2 sand/gallon), and snub and test.
5. With bottom of hole packed off, open tool between packers (3075-3125), test zone, break down with lease oil, treat formation with 10,000 gallons refined oil (1/2 sand/gallon).
6. Unsnub packers and raise tubing to set packers 3075-3075.
7. Test zone, break down with lease crude, treat with 10,000 gallons of refined oil (1/2 sand/gallon, snub and test.
8. Pull packers, rerun 2-inch tubing, test, and place back on production.

Approved **JUL 29 1955**
Except as follows: _____, 19____

Approved
OIL CONSERVATION COMMISSION
By **[Signature]**
Title **PRORATION MANAGER**

Humble Oil & Refining Company
Company or Operator
By **[Signature]**
Position **Agent**
Send Communications regarding well to:
Name **M. M. Rogers**
Address **Box 2347, Hobbs, New Mexico**

