

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON Sand-Oil Frac (Other)	<b>I</b>

October 14, 1954  
(Date)Hobbs, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Humble Oil & Refining Company  
(Company or Operator)Ada E. Thomas  
(Lease)Geackle Drilling Company  
(Contractor)

Well No. 5 in the NW 1/4 SW 1/4 of Sec. 24

T. 24S, R. 36E, NMPM, Cooper-Jal Pool, Lea County.

The Dates of this work were as follows: 10-7-54, 10-13-54

Notice of intention to do the work (was) ~~rescued~~ submitted on Form C-102 on September 15, 1954,  
(Cross out incorrect words)

and approval of the proposed plan (was) ~~was~~ obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Treated well through perforations from 3542 to 3548 with 4000 gallons refined oil and 4000# sand. Maximum pressure 2000#. Minimum pressure 1500#. Average injection rate 9 barrels per minute. Pumping through tubing and casing. Over flushed with 130 barrels oil. Shut in pressure after 2 minutes 1100#. Job complete 6:15 P.M. 10-7-54.

10-13-54: Treated well through perforations from 3542-3548 in 5-1/2" casing thru 2" tubing with 8000 gallons lease oil and 8000# sand by Halliburton. Breakdown pressure 2350# at injection rate of 12.8 bbls per minute. Maximum pressure 2200# at 13.8 bbls per minute. Minimum pressure 2000# at 14.8 bbls per minute. Final pressure 800#. Overflushed with 83 bbls oil. Total oil used in treatment 493 bbls. Pressure after 17 hours shut-in 150#, casing & tubing. Opened well, flowed 5.20 bbls oil.

Now swabbing.

Witnessed by E. D. Wolcott  
(Name)Humble Oil & Refining Company  
(Company)Tool Pusher  
(Title)

Approved:

OIL CONSERVATION COMMISSION

S. J. Stanley  
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: m m Ryzan

Position: District Superintendent

Representing: Humble Oil &amp; Refining Company

Address: Box 2347, Hobbs, New Mexico

-4-