6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-2000 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to the 6/12/95-6/16/95: Placed on injection and tested 6/17/95: Final test: 481 bbl water in 24 hours @ The original pressure chart was sent to the NMC 14. Ihereby certify that the foregoing is true and correct SIGNATURE	H with tubing and packer, TIH with plug and set @ 3300'. O'. TOC @ 2700'. Perforated casing with 2 jspf on intervi- le tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, 1 ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down.	al 3024'-3170' (164 holes). ISIP=970psi) Ind held for 30 minutes. ISIP=970psi) Ind held for 30 minutes. ISIP=970psi) Ind held for 30 minutes. ISIP=970psi) Ind held for 30 minutes. ISIP=970psi) Ind held for 30 minutes. ISIP=970psi) ISIP=970psi) IND MAMAGAR
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-2000 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to the 6/12/95-6/16/95: Placed on injection and tested 6/17/95: Final test: 481 bbl water in 24 hours @ The original pressure chart was sent to the NMC 14. I hereby certify that the foregoing is true and correct SIGNATURE TYPE OR PRINT NAME (This space for Federal or State office use)	A with tubing and packer, TIH with plug and set @ 3300'. D. TOC @ 2700'. Perforated casing with 2 jspf on Interview le tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, I ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down. DCD; a copy can be found on the reverse side of this form DCD; a copy can be found on the reverse side of this form TITLE_Engineering Assistant J. Carriger	al 3024'-3170' (164 holes). SIP=970psi) Ind held for 30 minutes. IND MAMAGORIA OCT 2 5 1995 OCT 2 5 1995 DIST. 6 N.M. Sbad, New Wett
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to to 6/12/95-6/16/95: Placed on injection and tested 6/17/95: Final test: 481 bbl water in 24 hours @ The original pressure chart was sent to the NMC 14. I hereby certify that the foregoing is true and correct SIGNATURE TYPE OR PRINT NAME	A with tubing and packer, TIH with plug and set @ 3300'. D. TOC @ 2700'. Perforated casing with 2 jspf on Interview le tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, J ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down. DCD; a copy can be found on the reverse side of this form DCD; a copy can be found on the reverse side of this form TITLE_Engineering Assistant	al 3024'-3170' (164 holes). ISIP=970psi) Ind held for 30 minutes. INND MANAGER INND INND INND INND INND INND INND INND INND INND INND INND INND INND INND INND INND INND
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to the 6/12/95-6/16/95: Placed on injection and tested 6/17/95: Final test: 481 bbl water in 24 hours @ The original pressure chart was sent to the NMC	A with tubing and packer, TIH with plug and set @ 3300'. D. TOC @ 2700'. Perforated casing with 2 jspf on Interview le tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, J ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down. DCD; a copy can be found on the reverse side of this form DCD; a copy can be found on the reverse side of this form TITLE_Engineering Assistant	al 3024'-3170' (164 holes). ISIP=970psi) Ind held for 30 minutes. INND MANAGER INND INND INND INND INND INND INND INND INND INND INND INND INND INND INND INND INND INND
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to to 6/12/95-6/16/95: Placed on injection and tested 6/17/95: Final test: 481 bbl water in 24 hours @ The original pressure chart was sent to the NMC	A with tubing and packer, TIH with plug and set @ 3300'. O. TOC @ 2700'. Perforated casing with 2 jspf on intervi- le tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Prnax=2250psi, Pmin=550psi, AIR=5BPM, I ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down. DCD; a copy can be found on the reverse side of this form A. A. A	al 3024'-3170' (164 holes). ISIP=970psi) Ind held for 30 minutes. INND MANAGER INND INND INND INND INND INND INND INND INND INND INND INND INND INND INND INND INND INND
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to to 6/12/95-6/16/95: Placed on injection and tested 6/17/95: Final test: 481 bbl water in 24 hours @ The original pressure chart was sent to the NMC	A with tubing and packer, TIH with plug and set @ 3300'. O'. TOC @ 2700'. Perforated casing with 2 jspf on Intervi- le tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, I ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down.	al 3024'-3170' (164 holes). SIP=970psi) Ind held for 30 minutes. Ind held for 30 minutes. In
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to 1 6/12/95-6/16/95: Placed on injection and tested 6/17/95: Final test: 481 bbl water in 24 hours @	A with tubing and packer, TIH with plug and set @ 3300'. O'. TOC @ 2700'. Perforated casing with 2 jspf on Intervi- le tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, I ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down.	al 3024'-3170' (164 holes). SIP=970psi) Ind held for 30 minutes. Ind held for 30 minutes. In
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to 1 6/12/95-6/16/95: Placed on injection and tested 6/17/95: Final test: 481 bbl water in 24 hours @	A with tubing and packer, TIH with plug and set @ 3300'. O'. TOC @ 2700'. Perforated casing with 2 jspf on Intervi- le tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, I ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down.	al 3024'-3170' (164 holes). SIP=970psi) Ind held for 30 minutes. Ind held for 30 minutes. In
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to 1 6/12/95-6/16/95: Placed on injection and tested 6/17/95: Final test: 481 bbl water in 24 hours @	A with tubing and packer, TIH with plug and set @ 3300'. O'. TOC @ 2700'. Perforated casing with 2 jspf on Intervi- le tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, I ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down.	al 3024'-3170' (164 holes). SIP=970psi) Ind held for 30 minutes. Ind held for 30 minutes. In
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to 1 6/12/95-6/16/95: Placed on injection and tested 6/17/95: Final test: 481 bbl water in 24 hours @	A with tubing and packer, TIH with plug and set @ 3300'. O'. TOC @ 2700'. Perforated casing with 2 jspf on Intervale tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, I ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down.	al 3024'-3170' (164 holes). SIP=970psi) Ind held for 30 minutes. Ind held for 30 minutes. In
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to 6/12/95-6/16/95: Placed on injection and tested 6/17/95: Final test: 481 bbl water in 24 hours @	A with tubing and packer, TIH with plug and set @ 3300'. O'. TOC @ 2700'. Perforated casing with 2 jspf on Intervale tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, I ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down.	al 3024'-3170' (164 holes). SIP=970psi) Ind held for 30 minutes. INND MANAGAR INND INNO I
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to 1 6/12/95-6/16/95: Placed on injection and tested 6/17/95: Final test: 481 bbl water in 24 hours @	A with tubing and packer, TIH with plug and set @ 3300'. O'. TOC @ 2700'. Perforated casing with 2 jspf on Intervale tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, I ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down.	al 3024'-3170' (164 holes). ISIP=970psi) Ind held for 30 minutes. ISIP=970psi) Ind held for 30 minutes. ISIP=970psi) Ind held for 30 minutes. ISIP=970psi) Ind held for 30 minutes. ISIP=970psi) Ind held for 30 minutes. ISIP=970psi) ISIP=970psi) IND MAMAGAR
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to the 6/12/95-6/16/95: Placed on injection and tested	H with tubing and packer, TIH with plug and set @ 3300'. O'. TOC @ 2700'. Perforated casing with 2 jspf on intervi- le tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, 1 ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down.	al 3024'-3170' (164 holes). SIP=970psi)
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to the 6/12/95-6/16/95: Placed on injection and tested	H with tubing and packer, TIH with plug and set @ 3300'. O'. TOC @ 2700'. Perforated casing with 2 jspf on intervi- le tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, 1 ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down.	al 3024'-3170' (164 holes). SIP=970psi)
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pack Notified Bonnie @ Hobbs OCD. Hooked up to the	H with tubing and packer, TIH with plug and set @ 3300'. O'. TOC @ 2700'. Perforated casing with 2 jspf on intervi- le tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, 1 ker and set @ 2962'. Pressure tested casing to 500psi ar water injection line. Rigged down.	al 3024'-3170' (164 holes). SIP=970psi)
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250 6/9/95: Released plug and TOH. TIH with pac	H with tubing and packer, TIH with plug and set @ 3300'. "With tubing and packer, TIH with plug and set @ 3300'. "TOC @ 2700'. Perforated casing with 2 jspf on intervi- te tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi, Pmin=550psi, AIR=5BPM, ker and set @ 2962'. Pressure tested casing to 500nsi ar	al 3024'-3170' (164 holes). SIP=970psi)
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick Acid treated with 5000g 15% NEFE HCL + 250	H with tubing and packer, TIH with plug and set @ 3300'. 0'. TOC @ 2700'. Perforated casing with 2 jspf on intervi 1e tubing with 600g 7-1/2% NEFE HCL + 150g Xylene. ball sealers (Pmax=2250psi Pmin=550psi AIR=58PM	al 3024'-3170' (164 holes). SIP=970psi)
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOF 6/7/95: Ran GR-CBC-CCL log from 3300'-200 6/8/95: TIH with packer and set @ 2962'. Pick	H with tubing and packer, TIH with plug and set @ 3300'. 7. TOC @ 2700'. Perforated casing with 2 jspf on intervalue tubing with 600g 7-1/2% NEFE HCL + 150g Xylene	al 3024'-3170' (164 holes).
6/5/95: MIRU. 6/6/95: Released packer and install BOP. TOP	i measured and true vertical depths for all markers and zones p 1 with tubing and packer. TIH with plug and set (3300)	
directionary united, give substitute locations and	measured and true vertical depths for all markers and zones p	ertinent to this work,)*.
directionally drilled, give subsurface locations and	measured and true vertical depths for all markers and zonce n	erlinent to this work)*
13. Describe Proposed or Completed Operations (Clu	early state all pertinent details, and give pertinent dates, includin	g estimated date of starting any proposed work. If well is
		(Note: Report results of multiple completion on Wall Completion or Recompletion Report and Log Form,)
	OTHER: Perf. Jalmat (acc. WF	X-671) Dispose Water
Final Abandonment Notice	Altering Casing	Conversion to Injection
Subsequent Report	Casing Repair	Water Shut-Off
Notice of Intent	Plugging Back	
	Abandonment Recompletion	🛄 Change or Hans 🦟
	Abandonment	
TYPE OF SUBMISSION	e Box(s) To Indicate Nature of Notice, R	
12. Check Appropriat	a Box(s) To Indicate Nature of Nation	
EAST Line Section 24	Township <u>24S</u> Range <u>36E</u>	LEA , NEW MEXICO
		11. Couple or Parish. State
Unit Letter I : 2310 Feet From	The SOUTH Line and 990 Feet From The	LANGLIE MATTIX TRVRS Q GRAYBURG
4. Location of Well (Footage, Sec., T., R., M., or Surv	vey Description)	10. Field and Pool, Exploratory Area
P.O. BOX 730, H	OBBS, NM 88240 397-0426	9. API Well No. 30 025 09639
3. Address and Telephone No.	RATION & PRODUCTION INC.	132
2. Name of Operator		
1. Type of Well: OIL GAS WELL WELL		8. Well Name and Number COOPER JAL UNIT
		7. If Unit or CA, Agreement Designation
	N FOR PERMIT " for such proposals	6. If Indian, Alottee or Tribe Name
	to drill or to deepen or reentry to a different reservoir.	LC 063965
SUNDRY NOTIC	ES AND REPORTS ON WELLS	5. Lease Designation and Serial No.
		Expires: March 31, 1993
BUREAU		Budget Bureau No. 1004-0135
	IENT OF THE INTERIOR DF LAND MANAGEMENT	
June 1990) DEPARTM		HOBBS, NEW MEXICO 88240 FORM APPROVED
(June 1990) DEPARTM	IENT OF THE INTERIOR	FORM APPROVED





• •