NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOSSS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

1005 MAR (19) FN 1:14

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the C

	Indicate Nature of Report by Checking	Below	
EPORT ON BEGINNING PRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL	
EPORT ON RESULT F PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON Clean out (Other) and Frac	x
	March 28, 1955	Midland, Tex	
Following is a report on the work do	ne and the results obtained under the heading	·	
Western Natural Gas Compan	ny.	Dunn B	
• • • • • • • • • • • • • • • • • • • •	, Well No	(Lease)in the NW 1/4 NE 1/4 of Sec	. 24
24S , R 36E , NMPM., La	nglie Mattix Pool,	Lea	Count
	rch 18, 1955 to March 24, 1959		
	D ACCOUNT OF WORK DONE AND RESI		
Killed well with oil. circulation. Sand-Oil	Cleaned out to a depth of 3505 fractured open hole with 10,00 gal. temporary plugging mate	by means of reverse	
Killed well with oil. circulation. Sand-Oil	Cleaned out to a depth of 3505	by means of reverse	
Killed well with oil. circulation. Sand-Oil	Cleaned out to a depth of 3505	by means of reverse	
Killed well with oil. circulation. Sand-Oil	Cleaned out to a depth of 3505	by means of reverse	
Killed well with oil. circulation. Sand-Oil	Cleaned out to a depth of 3505	by means of reverse	
Killed well with oil. circulation. Sand-Oil : 10,000# sand. Used 500	Cleaned out to a depth of 3505 fractured open hole with 10,00 gal. temporary plugging mate	by means of reverse C gal. lease oil and crial (Formjel).	
Killed well with oil. circulation. Sand-Oil	Cleaned out to a depth of 3505	by means of reverse C gal. lease oil and crial (Formjel).	er
Killed well with oil. circulation. Sand-Oil in 10,000# sand. Used 500	Cleaned out to a depth of 3505 fractured open hole with 10,00 gal. temporary plugging mate Western Natural Gas Co (Company) I hereby certify the to the best of my leading to the best of my leading to the best of the control of t	ompany Division Engine Of the information given above is true and	
Killed well with oil. circulation. Sand-Oil i 10,000# sand. Used 500 tnessed by C. H. Carr (Name)	Cleaned out to a depth of 3505 fractured open hole with 10,00 gal. temporary plugging mate Western Natural Gas Co (Company) I hereby certify that to the best of my 1	ompany Division Engine Of the information given above is true and	