Submit 3 Copies

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

to Appropriate District Office

P.O. Box 1980, Hobbs, NM 88240

DISTRICT I OLL CONSERVATION DIVISION WELL API NO. P.O. Box 2088 30 025 <del>09656</del>-DISTRICT II Santa Fe, New Mexico 87504-2088 P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease FEE X STATE L DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. SUNDRY NOTICES AND REPORTS ON WELLS ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: Cooper Jal Unit WELL | OTHER Injection Well 2. Name of Operator 8. Well No. Texaco Exploration and Production Inc. 241 3. Address of Operator 9. Pool name or Wildcat P. O. Box 730 Hobbs, NM 88240 Jalmat Tansill Yates 7 Rvs Well Location 1650 1560 Feet From The N Unit Letter \_ 1650 Feet From The E Line and Line County Section 25 Township Range 36E **NMPM** 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3288' KB Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON ... REMEDIAL WORK **ALTERING CASING** TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB X OTHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 06-28-93 - 07-07-93 1) Ran 2 3/8" injection tubing w/4 1/2" packer set @ 2930' 2) Test annulus to 500#, did not hold. 3) Pulled injection equipment, set CIBP @ 2930' cap w/1sx cmt, ran workstring w/packer. 4) Test various intervals, confirm hole @ 769' w/casing inspection log. 5) Halliburton squeezed hole w/40 sacks micro mattrix cement. 6) Wait on cement 93 hrs. 7) Drill cement 469'- 808', test casing, held OK. 8) Clean out to 3312' (PBTD). 9) Ran cement lined injection tubing, set packer @ 2938', test casing 300# 30 min, held OK. (Chart attached, copy on reverse side) 07-23-93: Inject 118 BWPD @ 680# (Prior rate: 0 BWPD @ 700#) I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE \_\_\_ TITLE Engr Asst DATE 09-08-93 TYPEORPRINT NAME L.W. Johnson TELEPHONE NO.505-393-7191 (This space for State Use) ORIGINAL SIGNED BY JERRY SEXTON

TITLE

DISTRICT I SUPERVISOR

TW.C.B

APPROVED BY \_

CONDITIONS OF APPROVAL, IP ANY:

DATE

