

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Santa Fe, New Mexico

April 27, 1956

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

W. S. Harrison

Summit Oil & Refining Company

(Company or Operator)

Well No. 1

in

(Unit)

1/4 of Sec. 14

T. 24-S

R. 24-S

NMPM,

Pool

County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

To undertake W. S. Harrison 1 as follows:

1. Run in unit and pull tubing.
2. Run sucker rod and change any logs.
3. Perforate casing at depth indicated from casing log.
4. Run 4-inch tubing with sucker packer and bridge plug.
5. Set bridge plug below lower perforations and set packer between perforated intervals.
6. Perforate lower perforations down 4-inch tubing with 10,000 gal. ref. oil and 10,000 gal.
7. Set bridge plug between perforated intervals and set packer above upper perforations.
8. Perforate upper perforations with 10,000 gallons of refined oil and 10,000 pounds sand.
9. Pull 4-inch tubing and run 2-inch tubing.
10. Shut well to clean up and place back on production.

Approved \_\_\_\_\_, 19\_\_\_\_  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By: *W. S. Harrison*

Title: *Oil & Gas*

Summit Oil & Refining Company

Company or Operator

By: *R. M. Austin*

Position: *Agent*

Send Communications regarding well to:

Name: *W. S. Harrison*

Address: *Box 2347, Santa Fe, New Mexico*