NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

5 61 7:41

Box 1071, Midland,

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

| nstructions in th | he Rules and Regulati | ons of the Commission. Indicate Nature of | Report by Checkin | g Below | | | | |
|-----------------------------|---------------------------|--|---------------------------------|---------------|--------------------------|--------------|---|----------|
| REPORT ON B Drilling op: | | REPORT ON R OF CASING SH | ESULT OF TEST | | REPORT ON REPAIRING V | WELL | | |
| REPORT ON F | RESULT G WELL | REPORT ON ROPERATION | ECOMPLETION | Х | REPORT ON (Other) | | | |
| | | 10 | 0/7/54 | | Midl | and, | Texas | |
| | | (1 | Date) | | | | (Place) | |
| | | rk done and the results obta A PETROLEUM CORI | | ling note | d above at the Harris | on | | |
| | own Westernesser | | | | (Lew) | | | |
| 245 | 36E (Contrac | tor) Cooper-Jal | , Well No | Te | in the | | ¼ of Sec | ·····, |
| Γ, R | , NMPM., | Cooper-Jal | Pool, | /c- lı | | | *************************************** | County. |
| | | | | | | | | |
| NT .* C ** | C 100 | G-102 on(Cross out incorrect words) | | | | | | |
| | | | form G-102 on | (Cr | oss out incorrect wor | ds) | ••••••• | , 19, |
| and approval of | the proposed plan (w | as) (was not) obtained. | | | e | | | |
| | DET | AILED ACCOUNT OF WO | RK DONE AND R | ESULTS | S OBTAINED | | | |
| 1. | Set Baker | bridge plug @ 3 | 1271. | | | | | |
| 2, | Gun perfora 3366-3382, | ated with 6- 5/8 and 3296-3310'. | B" bullets/ | foot | intervals: | 3 396 | 5-3412, | • |
| 3. | gals oil as 3366-3382 6 | n selective frac nd 2,000# sand. @ 6500 psi. Fra 2,000# sand. | Attempted | to b | reak down | inte | erval | |
| 4. | Set Baker : cementer a | retrievable brid t 2960'. | ige plug @ | 3 415' | and Bake | r ret | rievab | le |
| Pla | uns are to fi | low back load of | 11 and test | sand | s above. | Addi | itional | _ |
| _ | rfs. may be to E.H.Ir | required. win | SO.CAL.PE | T.COR | iP. | Sເ | upt. | |
| Witnessed by | (Name | | (Company) | ••••• | •••••• | (Title) | | |
| Approved: | IL CONSERVATION | COMMISSION | I hereby cert to the best of | | ne information giv | en above | is true and | complete |
| | J. U. | inley | Name | | etroleum | Engi: | _ neer | |
| | (Nam. | | Position | S | O. CAL. PET | - | • | |

(Date)

(Title)