

NE MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	Report of Perforating Casing	X

Eunice, New MexicoFebruary 27, 1938

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum CorporationN. EverettWell No. 2 in the

Company or Operator

Lease

SE 1/4 SW 1/4of Sec. 26T. 24R. 36, N. M. P. M.,Cooper

Field,

Lea

County.

The dates of this work were as follows:

Notice of intention to do the work was [was not] submitted on Form C-102 on _____ 19____

and approval of the proposed plan was [was not] obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Total Depth 3438'. 7" Casing set at 3420'. Well was producing 24 barrels oil & 2400 barrels water per day before perforations. Baker cement retainer set at 3411' 55 sacks cement pumped into formation. Drilled out to 3425' and perforated w/ 10 shots from 3420'-3425'. Tested 8 b ls fluid per hour, 99% Water. Cemented back to 3413' w/ 6 sacks cement. Perforated with Lane-Wells Gun Perforator from 3363'-3413'. Production test after perforating: 245 barrels fluid, 44% Water through 1" open choke in 24 hours.

DUPLICATE

Witnessed by George Clark

Name

Noble Drilling Co.

Company

Tool-pusher

Title

Subscribed and sworn to before me this _____

2 day of March, 1938Lewis A. Manser

Notary Public

My Commission expires Dec. 21, 1940

I hereby swear or affirm that the information given above is true and correct.

Name J. K. LewisPosition Sup'tRepresenting Amerada Petroleum Corporation

Company or Operator

Address Eunice, New Mexico

Remarks:

Guy Shepard
Name

Inspector
Title

MAR 3 - 1938