


N. *R36E*NEW MEXICO STATE LAND OFFICE
SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST

WELL RECORD

Mail to State Geologist, Santa Fe, New Mexico, not more than ten days
after completion of well. Indicate questionable data by fol-
lowing it with (?). Submit in duplicate.

Company *Amerada Pet. Corp.* Address *Hoobs, New Mexico - Drawer "0"*
Send correspondence to *J. J. Starkey* Address *Hoobs, New Mexico - Drawer "0"*
Verett Lee Well No. *2* in *1/4* of Sec. *6* T. *34S*
R. *36E*, N. M. P. M., Oil Field *Lee* County.
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is *Verett* Address *Hoobs, New Mexico*
The lessee is *Amerada Petroleum Corporation* Address *Wichita, Oklahoma*
If not state or patented land, give status
Drilling commenced *January 22, 1935* Drilling was completed *February 27, 1935*
Name of drilling contractor *Hoble Drilling Co.* Address *Wichita, Oklahoma*
Elevation above sea level at top of casing *3295* feet.
The information given is to be kept confidential until *no request* 19

OIL SANDS OR ZONES

No. 1, from *3422'* to *3436'* No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

No. 1, from *None* to No. 3, from to
No. 2, from to No. 4, from to

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATED		PURPOSE
							FROM	TO	
<i>12 1/2"</i>	<i>50</i>	<i>8</i>	<i>welded</i>	<i>150'</i>	<i>Larkin</i>				
<i>9 5/8"</i>	<i>40</i>	<i>8</i>	<i>spang</i>	<i>1419'</i>	<i>Larkin float</i>				
<i>7"</i>	<i>24</i>	<i>10</i>	<i>seamless steel</i>						
				<i>3420'</i>	<i>aker</i>				

MUDDING AND CEMENTING RECORD

SIZE	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
<i>12 1/2"</i>	<i>150'</i>	<i>150</i>	<i>alliburton</i>		
<i>9-5/8"</i>	<i>1419'</i>	<i>500</i>	<i>alliburton</i>		
<i>7"</i>	<i>3420'</i>	<i>200</i>	<i>alliburton</i>		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

SHOOTING RECORD

SIZE	SHELL USED	EXPLOSIVE USED	QUANTITY	DATE	DEPTH SHOT	DEPTH CLEANED OUT

TOOLS USED

Rotary tools were used from *0* feet to *3436'* feet, and from feet to feet
Cable tools were used from *None* feet to feet, and from feet to feet

PRODUCTION

Put to producing *February 28, 1935*
The production of the first *7 1/2* hours was *11 minutes* barrels of fluid of which *99.5* % was oil;
emulsion; *0.5* % water; and *0.5* % sediment. Gravity, Be *28.2*
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

L. Forcher, Driller *L. Starkey*, Driller
J. Johnson, Driller *W. J. King*, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work
done on it so far as can be determined from available records.

Subscribed and sworn to before me this *11* Name *J. L. Starkey*
day of *March*, 19*35* Position *Driller*
Bernard M. Stodghies Notary Public. Representing *Amerada Petroleum Corporation*
My commission expires *Jan. 2, 1939*

DUPLICATE

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	17	17	Caliche
17	131	114	Caliche cement
131	150	19	Red bed
150	220	70	Lime shells
220	330	110	Lime shells & red bed
330	529	199	Sand & lime shells
529	757	228	Red Beds & sand
757	875	118	Red bed
875	1018	143	Red beds & lime shell
1018	1124	106	Shale & lime shells
1124	1190	66	Shale & lime shells
1190	1208	18	Red bed
1208	1247	39	Shale & anhydrite
1247	1324	77	Anhydrite & broken lime
1324	1344	20	Anhydrite
1344	1416	72	Broken anhydrite & salt
1416	1419	3	anhydrite anhydrite
1419	2218	799	Anhydrite & salt
2218	2400	182	Salt
2400	2530	130	Salt, anhydrite & shells
2530	2557	27	Broken anhydrite, salt & streaks of gypsum
2557	2625	68	Salt
2625	2679	54	Anhydrite
2679	2717	38	Anhydrite & salt
2717	2855	138	anhydrite & gypsum salt
2855	2889	34	Anhydrite & gyp
2889	2952	63	Anhydrite & lime
2952	2992	40	Lime
2992	3011	19	Anhydrite & lime
3011	3035	24	Brown lime
3035	3062	27	Lime & anhydrite
3062	3085	23	Hard lime
3085	3160	75	Lime
3160	3185	25	Gray lime
3185	3223	38	Lime
3223	3435	212	Lime
	3438	3	Steel line measurement showed total depth to be 3438'