

FORM C-102
DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

RECEIVED
FEB 9 - 1941
RECEIVED
HOBBS OFFICE

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL X	

Hobbs, New Mexico

2/2/40

Place

Date

OIL CONSERVATION COMMISSION
Santa Fe, New Mexico.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Tide Water Associated Oil Company. C.D. Woolworth Well No. **1** in the
Company or Operator Lease

SE 1/4 of Sec. **26**, T. **24**, R. **36**, N. M. P. M.,

Cooper Field, **Lea** County

The dates of this work were as follows: **2/1/40**

Notice of intention to do the work was ~~XXXXXX~~ submitted on Form C-102 on **3/8/39** 19____
and approval of the proposed plan was ~~XXXXXX~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Well was plugged to above all perforations in casing with cement. Casing shot off and pulled at 2225'. Cemented at top of salt and surface W/35-sacks cement, W/heavy mud between plugs. Was unable to recover any of intermediate string which was cemented at 1496' to surface W/850-sacks cement. Location is leveled, and regulation marker erected. Actual footage that was recovered on the 7" OD Casing was 2214'-5" (73-Joints)

Witnessed by **Lloyd Lamb** **Tide Water Assoc Oil Co.** **Foreman**
Name Company Title

Subscribed and sworn to before me this

3 day of **February**, 19 **40**

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name **Lloyd Lamb**

Position **Foreman**

Representing **Tide Water Assoc Oil Co**
Company or Operator

My Commission expires **November 22, 1941**

Address **Drawer KK, Hobbs, New Mexico**

Remarks:

Roy Garbrough
Name
OIL & GAS INSPECTOR
Title