


NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

DUPLICATE

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	Report on squeeze job. X

Hobbs, New Mexico

3/31/38

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Tide Water Assoc Oil Company. C.D. Woolworth "A" Well No. 1 in the

Company or Operator **SEA** of Sec. **26**, T. **24**, R. **36**, N. M. P. M.,
Field, **Copper** County, **Lea**

The dates of this work were as follows:

Notice of intention to do the work was [~~XXXX~~] submitted on Form C-102 on **3/26/38** 19____
and approval of the proposed plan was [~~XXXX~~] obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

After setting Baker Cement Retainer at 3245' W/75-sacks cement plugging off old casing perforations which was 3282' - 3368' W/20-holes, we perforated casing again from 3368' - 3369' W/20-holes by the Lane-Wells Perforating Gun with Packer set at 3390'. Then we swabbed down to 1800' and were unable to lower fluid any more, tubing was then raised 10' and re-set Packer, fluid was then swabbed down within 800' of bottom, fishing for swab now, preparing to treat with acid, as well is swabbing 100% water with very little gas. Water coming in at the rate of 2-bbls per hour.

Witnessed by **Lloyd Lamb** Tide Water Assoc Oil Company.
Name Company Title

Subscribed and sworn to before me this

31 day of March, 1938

Lance Sparks
Notary Public

My Commission expires November 22, 1941.

I hereby swear or affirm that the information given above is true and correct.

Name *Edmund ...*Position **Prod. Sup't.**Representing **Tide Water Assoc Oil Company**Address **Drawer KK, Hobbs, New Mexico.**

Remarks:

Gary Shepard
Name
Oil & Gas Inspector
Title