


## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES



Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL	

\_\_\_\_\_, New Mexico \_\_\_\_\_, 1946  
Place Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the \_\_\_\_\_

~~Phillips Petroleum Company~~ C. D. Woolworth Well No. \_\_\_\_\_ in NW  
Company or Operator Lease  
of Sec. 26, T. 24 S., R. 36 E., N. M. P. M., \_\_\_\_\_ Field,  
Los \_\_\_\_\_ County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

P. B. T. D. 3340'. 7" casing perforated from 3300' to 3320'. Casing set at 3435'.  
9 5/8" casing set at 3363'. 12" casing set at 2270'.

Fill hole with heavy mud to 3340'. Run cement plug 7" to 3200'. Shoot 7" casing, starting at approximately 2800' and shoot upward at 100' intervals until casing is free. After pulling 7" casing, fill hole with heavy mud.

Start shooting 9 5/8" casing at 500' and shoot at 100' intervals upward until casing is free. After pulling 9 5/8", run 55' cement plug (40 sacks) on top of 9 5/8" casing, fill hole with heavy mud to within approximately 10' of surface and complete plugging with 10' cement cap and standard steel pipe marker.

Approved \_\_\_\_\_, 19\_\_\_\_  
except as follows:

Phillips Petroleum Company or Operator

By

Position

Send communications regarding well to

Name

Address

OIL CONSERVATION COMMISSION

By

Title