

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	09683 30-025-9683
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	WOOLWORTH, C. D.
8. Well No.	009
9. Pool name or Wildcat	JALMAT

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER SWD	
2. Name of Operator Phillips Petroleum Company	
3. Address of Operator 4001 Penbrook Street, Odessa, TX 79762	
4. Well Location Unit Letter B : 660 Feet From The NORTH Line and 1980 Feet From The EAST Line Section 27 Township 24-S Range 36-E NMPM LEA County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3336' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. THIS IS A RULE 118 WELL.
2. MIRU SIERRA WELL SERVICE, NU BOPE, COOH W/ ALL INJECTION EQUIPMENT, GIH W/7" CIBP ON WS, SET @ 3300', CIRC 7" CSG W/9.5 PPB MUD LADEN FLUID.
3. ALL CEMENT PLUGS ARE CLASS "C" MIXED AT 14.8 PPG
4. SPOT PLUG NO. 1 100 SXS, 3300'-2830', COVERS YATES & TANSILL.  
SPOT PLUG NO. 2, 25 SXS, 2200'-2100', COVERS TOC.
5. FREEPOINT 7" CSG & CUT, NEED TO PULL 1437'.
6. SPOT PLUG NO. 3, 70 SXS, 1487'-1337', WOC & TAG, COVER SALT TOP & 9-5/8" SHOE.
7. PERF 9-5/8" CSG @ 253', PUMP PLUG NO. 4, 175 SXS DOWN 9-5/8" CSG THRU PERFS @ 253' & BACK TO SURFACE ON 12-1/4" & 9-5/8" ANNULUS LEAVING THE 9-5/8" CSG FULL.
8. CUT OFF CSG, INSTALL MONUMENT MARKER, PERFORM RECLAMATION WORK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Larry M. Sanders TITLE Senior Regulation Analyst DATE 04/18/96

TYPE OR PRINT NAME Larry M. Sanders TELEPHONE NO. (915)368-1488

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE APR 23 1996  
CONDITIONS OF APPROVAL, IF ANY: