


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

August 8, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Amerada Petroleum Corporation **N. Everett** Well No. **3** in the

Company or Operator **NB & SK** of Sec. **34**, T. **24S**, R. **36E**, N. M. P. M.,
Cooper Field, **Lea** County.

The dates of this work were as follows: **July 30, 1947 to August 6, 1947**

Notice of intention to do the work was (~~received~~) submitted on Form C-102 on **July 29** 19 **47**
and approval of the proposed plan was (~~received~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3495' Total Depth, Lime. Pulled rods and plugged 5 1/2" casing with 15 sacks common cement at 3370', July 31, 1947. Pulled tubing and shot off 5 1/2" casing with one 1 qt. shot of Nitroglycerin at 2775', August 1, 1947. Recovered 91 joints for 2886' 0". Took strain on 8-5/8" casing and casing parted at 199', 7 joints down. Could not fish successfully and plugged 8-5/8" casing from 360' to 295' with 18 sacks Trinity Common Cement and flushed with 15 barrels mud. Plugged 13" OD casing with 5 sacks Trinity Common Cement from 15' to 8'. 4" Pipe Marker 5' high placed in center of cement cap, August 6, 1947.

Witnessed by **K. V. Stephenson** **Amerada Petroleum Corporation** **Foreman**
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

8th. day of **August**, 19 **47**

Name **William J. James**

Will Hails Taylor
Notary Public

Position **Farm Boss**

Representing **Amerada Petroleum Corporation**
Company or Operator

*My commission expires _____

Address **Drawer D, Monument, New Mexico**

Remarks:

APPROVED

Date

Ros. Yachinovich
Name
Title