Form 9-381 a (Feb. 1961)	Budget Bureau No. 42-R368.4. Approval expires 12-31-60.
X	(SUBMIT IN TRIPLICATE) UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY
	GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING			
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) TEXACO In:., P. O. Box 352, I. B. Ogg "B" <u>Midland, Texas, August 29</u> , 19.60				
Nr. 1 K Sec. 34 24-S (4 Bec. and Bec. No.) (Twp.)	$\begin{array}{c c} \text{from} & \left\{ \begin{matrix} N \\ Sx \end{matrix} \right\} \text{ line and } \underbrace{O \cup O}_{\text{ft. from}} \text{ft. from} & \left\{ \begin{matrix} E \\ Sx \end{matrix} \right\} \text{ line of sec. } \underbrace{34}_{\text{(Mange)}} \\ \underbrace{O \cup O \\ (Meridian)} \\ \underbrace{A \\ O \cup O \\ (Meridian)} \\ \underbrace{O \cup O \\ (State or Territory)} \\ O \cup O \\ ($			

The elevation of the derrick floor above sea level is 3304. ft.

T*-

DETAILS OF WORK

	(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work)
	propose to plug and abandon subject well as follows: Pull rods, pump, and mud up hole.
2.	Spot 70 sx. cement plug from 36161 to 20181
3.	Spot 70 sx. cement plug from 3515' to 3218'. Cut 7" casing at 2400', recover same.
Ч° 6	7" casing.
5.	Spot 45 sx. cement plug from 1494' to 1394' inside 9 5/8" casing.
₩.	WWW EV DA. CRANNELL DIDLE IN RINKOAA
1.	Install 4" Dipe marker extending at shows surface and leave t
88	Install " pipe marker extending 4' above surface, and clean location per New Mexico Oil Conservation Commission regulations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.			
Company			
Address _2	· · · 1		
J. G. Blevins, Jr.	By		
Midland, Texas	TitleAstDistSupt		