NEW MEXICO STATE LAND OFFICE SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST

NOTICE OF INTENTION TO TEST WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in triplicate.

formation at a depth of	T D Thinton		N. M	ex.,	, 19.2.9
Isbad Isbarta Fr. New Mexico. Dear Sir: You are hereby notified that we intend to test the shut-off of water in Nugent Everett Well No. 1 in Cen.of/of Sec. 35 , T. 24S R. 36E N. M. P. M. Cooper Oil Field Lea County, on 11-7-34 19 9-5/8" in	Mr. J. D. Hallver,				
Dear Sir: You are hereby notified that we intend to test the shut-off of water in Nugent Everett Well No. 1 in Cen.of/of Sec. 35, T. 24S, R. 36E, N. M. P. M., COOPET Oil Field Lea County, on 11-7-34, 19 9-5/8" in 40# Ib. casing was { landed { in Anhyd.shel. formation at a depth of 1633 feet on 8FM 11-3-34 19 1000 sacks of El Toro & Lone Star Common cement were used. The method used in placing the cement was as follows: Halliburton Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: Additional information: Set and cemented 1633' of 9-5/8" 40\$ new seamless casing at 8FM 11- with 1000 sacks El Toro and Lone Star common cement. Halliburton process Cement returned to surface. Flug will be drilled and casing tested by p sure method at 8FM 11-7-34. Approved 19 Sincerely yours, Except as follows: MILLANCE		lovico			
You are hereby notified that we intend to test the shut-off of water in Nugent Everett Well No. 1. in Cen.of/of Sec. 35., T. 243., R. 368., N. M. P. M., COOPET Oil Field Lea County, on 11-7-34., 19. 9-5/8" in 404 lb. casing was landed formation at a depth of 1633 feet on 8FM 11-3-34 19. 1000 sacks of El Toro & Lone Star Common cement were used. The method used in placing the cement was as follows: Halliburton Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Additional information: Set and cemented 1633' of 9-5/8" 404 new seamless casing at 8FM 11- with 1000 sacks El Toro and Lone Star common cement. Halliburton process Cement returned to surface. Flug will be drilled and casing tested by p sure method at 8FM 11-7-34. Approved 19. Sincerely yours, Except as follows: Mathematical formation regarding well to Name Drawer K, Wink, Texas Address		lexico.			
Well No. in Cen.of/of Sec. 35. T 24.3 R 36E N. M. P. M. COOPPER Oil Field Lea County, on 11-7-34 19 9-5/8" in 40# ib. casing was landed (cemfented) in Anhyd.shell formation at a depth of 1633 feet on 8PM 11-3-34 19 19 1000 sacks of El Toro & Lone Star Conmon cement were used. The method used in placing the cement was as follows: Halliburton Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: feet and left undisturbed for at least Additional information: Set and cemented 1633' of 9-5/8" 40# new seamless casing at 8PM 11- with 1000 sacks El Toro and Lone Star common cement. Halliburton proces Cement returned to surface. Flug will be drilled and casing tested by p sure method at 8PM 11-7-34. 19 Sincerely yours, Except as follows: THE TEXAS CONPANY - Prod. Dept. Company or Operator. By Sinderely yours, Sinderely yours, Except as foll	You are hereby notifi	ed that we intend to	test the shut-off of v	ater in Nugent	Everett
on 11-7-34 , 19 9-5/8" in. 40# lb. casing was contended contended formation at a depth of 1633 feet on 8PM 11-3-34 in Anhyd.shel. formation at a depth of 1633 feet on 8PM 11-3-34 19 19 1000 sacks of El Toro & Lone Star Common cement were used. The method used in placing the cement was as follows: Halliburton Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: Additional information: Set and cemented 1633' of 9-5/8" 40 # new seamless casing at 8PM 11-with 1000 sacks El Toro and Lone Star common cement. Halliburton process Cement returned to surface. Plug will be drilled and casing tested by p sure method at 8PM 11-7-34. Approved 19 Sincerely yours, THE TEXAS CONFANY - Prod. Dept. Company or Operator. By Market Send communication regarding well to Name Drawer K, Wink, Texam Address Address	Well No1 in	$\frac{SE_4^1}{Of Sec.}$ of N	₩ ‡ , 7 , T	24 S., R.	<u>36e</u> ,
formation at a depth of	-				
1000 sacks of El Toro & Lone Star Conmon cement were used. The method used in placing the cement was as follows: Halliburton Fluid level will be bailed to a depth of feet and left undisturbed for at least feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: feet and left undisturbed for at least Additional information: Set and cemented 1633' of 9-5/8" 40 # new seamless casing at & EPM 11- with 1000 sacks El Toro and Lone Star common cement. Helliburton proces Cement returned to surface. Plug will be drilled and casing tested by p sure method at 8PM 11-7-34. Approved 19 Sincerely yours, Except as follows: THE TEXAS COMPANY - Prod. Dept. Company or Operator. By By Mathematical Sender of Diverses Name Drawer K, Wink, Texas Address	on 11-7-34 , 19	9-5/8" in.	40# lb. casing wa	$s \left\{ \begin{array}{c} \text{landed} \\ \text{g}_{c} \\ \text{cemented} \end{array} \right\} $ in	nhyd.shel
The method used in placing the cement was as follows: Halliburton Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: Additional information: Set and cemented 1633' of 9-5/8" 40 # new seamless casing at 8PM ll- with 1000 sacks El Toro and Lone Star common cement. Halliburton process Cement returned to surface. Flug will be drilled and casing tested by p sure method at 8PM ll-7-34. Approved 19 Sincerely yours, Except as follows: THE TEXAS CONPANY - Prod. Dept. Company or Operator. By MMAACA Position Divn. Supt. Send communication regarding well to Name Drawer K, Wink, Texat Address	formation at a depth of	1633	feet on 8PM	11-3-34	19
Fluid level will be bailed to a depth of	1000 sad	eks of El Toro 8	& Lone Star Com	on cement were	used.
12 hours before your inspection. Adjacent property owners have been notified as follows: Additional information: Set and cemented 1633' of 9-5/8" 40 # new seamless casing at 8PM ll- with 1000 sacks El Toro and Lone Star common cement. Halliburton proces Cement returned to surface. Plug will be drilled and casing tested by p sure method at 8PM 11-7-34. Approved 19 Sincerely yours, Except as follows: THE TEXAS COMPANY - Prod. Dept. Company or Operator. By Mathematical Position Divn. Supt. Send communication regarding well to Name Drawer K, Wink, Texes Address	The method used in pl	acing the cement wa	s as follows: Hall	burton	
12 hours before your inspection. Adjacent property owners have been notified as follows: Additional information: Set and cemented 1633' of 9-5/8" 40 # new seamless casing at 8PM ll- with 1000 sacks El Toro and Lone Star common cement. Halliburton proces Cement returned to surface. Plug will be drilled and casing tested by p sure method at 8PM 11-7-34. Approved 19 Sincerely yours, Except as follows: THE TEXAS COMPANY - Prod. Dept. Company or Operator. By Mathematical Position Divn. Supt. Send communication regarding well to Name Drawer K, Wink, Texes Address	Fluid lovel will be bei	led to a depth of	foo	t and laft undisturba	d for at loost
Adjacent property owners have been notified as follows: Additional information: Set and cemented 1633' of 9-5/8" 40 # new seamless casing at 8PM ll- with 1000 sacks El Toro and Lone Star common cement. Halliburton proces Cement returned to surface. Plug will be drilled and casing tested by p sure method at 8PM 11-7-34. Approved 19. Except as follows: Sincerely yours, Company or Operator. By Divn. Supt. Send communication regarding well to Name Drawer K, Wink, Texas Address		_	1ee	i and left undisturbe	u for at least
Additional information: Set and cemented 1633' of 9-5/8" 40 # new seamless casing at 8PM ll- with 1000 sacks El Toro and Lone Star common cement. Halliburton proces Cement returned to surface. Plug will be drilled and casing tested by p sure method at 8PM 11-7-34. Approved 19 Sincerely yours, Except as follows: THE TEXAS COMPANY - Prod. Dept. Company or Operator. By Manual Position Divn. Supt. Send communication regarding well to Name Drawer K, Wink, Toxam Address					
Additional information: Set and cemented 1633' of 9-5/8" 40 # new seamless casing at 8PM ll- with 1000 sacks El Toro and Lone Star common cement. Halliburton proces Cement returned to surface. Plug will be drilled and casing tested by p sure method at 8PM 11-7-34. Approved 19 Sincerely yours, Except as follows: THE TEXAS COMPANY - Prod. Dept. Company or Operator. By Managet Position Divn. Supt. Send communication regarding well to Name Drawer K, Wink, Texat Address	Adjacent property ow	vners have been not	ified as follows:		
Approved 19 Sincerely yours, Except as follows: THE TEXAS COMPANY - Prod. Dept. Company or Operator. Company or Operator. By Position Divn. Supt. Send communication regarding well to Name Drawer K. Wink, Texat Address Address	Additional information				
Except as follows: THE TEXAS COMPANY - Prod. Dept. Company or Operator. By Position Divn. Supt. Send communication regarding well to Name Drawer K. Wink, Texat Address	Set and cemente with 1000 sacks El S Cement returned to a	Foro and Lone surface. Plug	Star common ceme	ent. Halliour	con proces
Company or Operator. By Maria Company or Operator. By Position Divn. Supt. Send communication regarding well to Name Drawer K, Wink, Texas Address	Set and cemente with 1000 sacks El 3 Cement returned to sure method at 8PM 3	Foro and Lone surface. Plug 11-7-34.	Star common ceme ; will be drilled	ent. Halliour	ton proces
By B	Set and cemente with 1000 sacks El 3 Cement returned to sure method at 8PM 3	Foro and Lone surface. Plug 11-7-34.	Star common ceme ; will be drilled	ent. Halliour	ton proces
Position Divit. Sup. Send communication regarding well to Name Drawer K, Wink, Texas Address	Set and cemente with 1000 sacks El 5 Cement returned to sure method at 8PM 5 Approved	Foro and Lone surface. Plug 11-7-34. 19	Star common ceme will be drilled	and casing to	Dept.
Send communication regarding well to Name Drawer K, Wink, Texes Address	Set and cemente with 1000 sacks El 2 Cement returned to sure method at 8PM 2 Approved Except as follows:	Foro and Lone surface. Plug 11-7-34.	Star common ceme will be drilled	and casing to	Dept.
Name Drawer K, Wink, Texas Address	Set and cemente with 1000 sacks El 2 Cement returned to sure method at 8PM 2 Approved Except as follows:	Foro and Lone surface. Plug 11-7-34.	Star common ceme will be drilled Sincerely yours, THE TEXAS By	COMPANY - Prod.	Dept.
Address	Set and cemente with 1000 sacks El 2 Cement returned to sure method at 8PM 2 Approved	Foro and Lone surface. Plug 11-7-34.	Star common ceme will be drilled Sincerely yours, THE TEXAS By Position	COMPANY - Prod. Company Company Company Company Company ivn. Supt.	Dept.
T. J. VIANIK	Set and cementer with 1000 sacks El 2 Cement returned to sure method at 8PM 2 Approved	Foro and Lone surface. Plug 11-7-34.	Star common cene will be drilled Sincerely yours, THE TEXAS By Position D Send communicat	COMPANY - Prod. Company Company Company Company ivn. Supt.	Dept.
State Geologist or Oil and Tas Inspector.	Set and cementer with 1000 sacks El 2 Cement returned to sure method at 8PM 2 Approved	Foro and Lone surface. Plug 11-7-34.	Star common cene will be drilled Sincerely yours, THE TEXAS By Position D: Send communicat Name Drawer.	COMPANY - Prod. Company Company Company Company Company ivn. Supt.	Dept.
	Set and cementer with 1000 sacks El 2 Cement returned to sure method at 8PM 2 Approved	Foro and Lone surface. Plug 11-7-34.	Star common cene will be drilled Sincerely yours, THE TEXAS By Position D: Send communicat Name Drawer.	COMPANY - Prod. Company Company Company Company Company ivn. Supt.	Dept.

and and a start of the second s The second start of the second st

自己和自己的 医乳肉的 医马马氏 经公司 法正式 计分析 经利用 法复数权

•

1 1

an <u>a</u>n baran baran B^{ar}an Baran Ba

t i standar

¹ States and a second secon second sec

.

•

 $\mathcal{L}_{\mathcal{L}} = \mathcal{L}_{\mathcal{L}} = \mathcal{L}_{\mathcal{L}} = \mathcal{L}_{\mathcal{L}}$

1. 1997 - A. 1997 - A