

Form 3160-3
(June 1990)

RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCT 7 10 35 AM '92

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
AREA Use "APPLICATION FOR PERMIT—" for such proposalsFORM APPROVED
Budget Bureau No. 1004-0125
Expires: March 31, 1993

5. Lease Designation and Serial No.

NMLC052618A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Convast Energy Corporation

3. Address and Telephone No.

2401 Fountain View Dr., Suite 700, Houston, TX 77057

4. Location of Well (Section, Sec., T., R., M., or Survey Description)

600' FNL & 1980' FEL, Sec 35, T24S, R36E ✓

8. Well Name and No.

I.B. Org A-2

9. API Well No.

300250970100S1

10. Field and Pool, or Exploratory Area

Jalmat

11. County or Parish, State

Lea Co., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐
- Notice of Intent
-
- ☒
- Subsequent Report
-
- ☐
- Final Abandonment Notice

TYPE OF ACTION

- ☒
- Abandonment
-
- ☐
- Recompletion
-
- ☐
- Plugging Back
-
- ☐
- Casing Repair
-
- ☐
- Altering Casing
-
- ☐
- Other

- ☐
- Change of Plans
-
- ☐
- New Construction
-
- ☐
- Non-Routine Fracturing
-
- ☐
- Water Shut-Off
-
- ☐
- Conversion to Injection
-
- ☐
- Dispose Water

(Note: Report results of multiple completion on well Completion or Recompletion Report Add Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent data, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and name pertinent to this work.)

- 1) Spotted plug #1 from 3163-3108' w/ 35 sx. Tagged w/ tbg.
- 2) Displaced hole w/ 9.0 ppg mud.
- 3) Perfd @ 1675'.
- 4) Spotted plug #2 from 1719-1595' w/ 75 sx. Tagged w/ tbg.
- 5) Perfd @ 219'.
- 6) Spotted plug #3 from 219' to surface w/ 165 sx.
- 7) Cut off csgs & welded on dry hole marker.
- 8) Cleaned & leveled location. P&A 9/2/92.

Approved as to plugging of the well core.
Liability under bond is returned until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Theresa QuinterTitle Engineering TechnicianDate 9/30/92

(This space for Federal or State office use)

Approved by Alfonso S. SanchezTitle SupervisorDate 10/20/92

Conditions of approval, if any: