

Form 9-431
Dec. 1973**ROSWELL DISTRICT COPY**Form Approved.
Budget Bureau No. 42-R1424**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY****SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☐ well ☐ other Salt Water Disposal

2. NAME OF OPERATOR

ConVest Energy Corporation

3. ADDRESS OF OPERATOR

c/o Oil Reports & Service, Inc. Box 763, Hobbs,

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FSL & 1980 FEL of Sec. 35

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☐☒

5. LEASE

LC-032618-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

I. B. Ogs "A"

9. WELL NO.

5

10. FIELD OR WILDCAT NAME

Jalmar

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 35, T24S, R36E

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

AUG 12 51 PM
RECEIVED
BUREAU OF LAND MANAGEMENT
ROSWELL DISTRICT

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Found 7" casing parted at 2685. Set retainer at 2530, opened 9 5/8" bradenhead. Circulated 200 bbls water with 3 sacks Floeal. Pumped 850 sacks cement. Dumped 50 sacks cement on top of retainer. Ran temperature survey, found top cement behind 7" at 2377 and top of plug at 2430. Perf 4 holes at 1100, loaded hole & broke circulation with 45 bbls water. Ran retainer, retainer hung at 323'; set retainer at 323'. Broke circulation with 40 bbls water. Pumped 123 sacks below retainer. Filled 7" casing above retainer to surface with 46 sacks. Used 1 sack cement to fill in around well head & plant 4" x 4" marker. Well P&A 6/14/83. Plugging operations witnessed by Walter Cox.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____

FL

18. I hereby certify that the foregoing is true and correct

SIGNED

Donna Hobbs

TITLE

Agent

DATE

8/3/83

APPROVED _____
CONDITIONS OF APPROVAL, IF ANY:This space for Federal or State office use:
AREA _____

TITLE

CARLSBAD RESOURCE AREA

DATE

8-11-86

OK

*See instructions on Reverse Side

TOTAL P.04