


(SUBMIT IN TRIPLICATE)

U. S. Land Office **Las Cruces**

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Lease or permit No. **032618**



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas February 6, 1945

I.B.Ogg (a)

Well No. **6** is located **660** ft. from **MM** line and **1980** ft. from **E** line of sec. **35**

SE 1/4 Sec. 35

(1/4 Sec. and Sec. No.)

24-S

(Twp.)

36-E

(Range)

N.M.P.M.

(Meridian)

Cooper

(Field)

Lea

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is **3275** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

See attached sheet.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **The Texas Company**

Address **Box 1270**

Midland, Texas

By

Otto Chavira

Title **Drlg. & Prod. Foreman**

I. B. Cgg (a) Well No. 6

This well was completed 4-15-35 and produced until January 1936 when it was necessary to attempt remedial work in an effort to re-complete as a commercial well.

The well was plugged back in stages from 3480' to 3265' in many attempts to recomplete as reported by Sundry Notices & Reports on Wells. The 1st report dated 8-13-37 gives the results of the final work on this well and the well has been standing since that time.

The 7" casing is cemented at 3350' with 150 sacks and has been perforated from 3125' to 3264' and from 2955 to 3050' and shot with 50 quarts from 3149 to 3264'. We propose to salvage as much 7" casing as possible and plug and abandon well as follows:

1. Plugged back with 65 sacks cement from 3265 to 2940'
2. Part and pull all possible (approximately 2000') of 7" casing.
3. Spot cement plug 30 sacks in bottom of 9-5/8" casing from 1760' to 1695' (9-5/8" cemented at 1726' with 1350 sacks).
4. Cement customary 4" pipe marker in top of hole with 20 sacks.
5. Hole will be filled with heavy mud between cement plugs and all mud and cement will be spotted by pumping in through tubing.