NEW MEXICO STATE LAND OFFICE SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST

NOTICE OF TEST OF WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible.

If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in duplicate.

State Geologist, Santa Fe, New Mexico. Dear Sir: You are hereby notified that we intend to test the shut-off of water in Well No. 1 in of Sec. 35 , T. 249 , R. 568 N. M. P. M., Jal, N. Mor Oil Field Lea County, on Dec. 20th, 19 24 . 36 lb. casing was comented in Anhydrite formation at a depth of 1607 feet on December 15th 19 54 1000 sacks of El Toro Common cement were used. The method used in placing the cement was as follows: Halliburten Plug method Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: The Toxas Company Additional information: 1400# Pressure applied and allowed to stand for one hours Except as follows: Sincerely yours. Except as follows: Sincerely yours. Send communication regarding, well to Name In Jack Instituted Address Licence In Manual Licence In Name In Jack Instituted In Name Instituted		,		Ial	N. N	lex., Decem	der 15th	19.54
Santa Fe, New Mexico. Dear Sir: You are hereby notified that we intend to test the shut-off of water in Youlworth Well No. 1 in of Sec. 35 , T. 24S , R. 36E N. M. P. M., Jal, N. Mox Oil Field Lea County, on Dec. 20th, 19 34 36 lb. casing was cemented cemented commation at a depth of 1607 feet on December 15th 19 34 1000 sacks of El Toro Common cement were used. The method used in placing the cement was as follows: Halliburton Plug method Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: The Toxas Company Additional information: 1400\$ Pressure applied and allowed to stand for one hour. By Angle	Mr. E. H. We	lle						
You are hereby notified that we intend to test the shut-off of water in Well No. 1 in of Sec. 35 , T. 24S , R. 36K N. M. P. M., Jal, N. Mox Oil Field Lea County, on Dec. 20th, 19 34 . 36 lb. casing was cemented cemented cemented formation at a depth of 1607 feet on December 15th 19 34 1000 sacks of El Toro Common cement were used. The method used in placing the cement was as follows: Hallburton Plug method Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: 1400f Pressure applied and allowed to stand for one hour. Approved 19 Sincepely yours. Except as follows: Dec. 20th, R. 36K County, R. 36K County, In Anhydrite cemented in Anhydr			co.					
Well No. 1 in of Sec. 35 , T. 24S , R. 36E , N. M. P. M., Jal, N. Max Oil Field Lea County, on Dec. 20th. 19 34 . 36 lb. casing was cemented common at a depth of 1607 feet on December 15th 19 34 . 1000 sacks of El Toro Cosmon cement were used. The method used in placing the cement was as follows: Halliburton Plug method Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: The Toxas Company Additional information: 1400f Pressure applied and allowed to stand for one hours Except as follows: Position Lux, Long County, T. 24S , R. 36E , N.	Dear Sir:						• ••	
N. M. P. M., Jal, N. Mex Oil Field Lea County, on Dec. 20th, 19 54. 36 lb. casing was commented formation at a depth of 1607 feet on December 15th 19 54 1000 sacks of El Toro County cement were used. The method used in placing the cement was as follows: Hallibarten Plug method Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: The Toxas Company Additional information: 1400\$ Pressure applied and allowed to stant for one hours Except as follows: By A. Je A. Mary County County Position Carry Company or Operator. By A. Je A. Mary County County Position Carry County Position Carry County County Position Carry County Coun	You are hereb	y notified th	hat we intend to	test the shut	off of	water in	oolworth	
formation at a depth of 1607 feet on December 15th 19 54 1000 sacks of El Toro Common cement were used. The method used in placing the cement was as follows: Halliburten Plug method Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: The Toxas Company Additional information: 1400f Pressure applied and allowed to stand for one hours Except as follows: By A. Jelmand. Position Day T.	Well No. 1	in	of Sec	35	, Т	24 S	, R. 56	B ,
formation at a depth of 1607 feet on December 15th 19 54 1000 sacks of El Toro Common cement were used. The method used in placing the cement was as follows: Halliburton Plug method Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: The Toxas Company Additional information: 14004 Pressure applied and allowed to stand for one houre Except as follows: Decemented processed 19 54 Sincepely yours. Company or Operator. By J. Je J. J. Position L. 1.	N. M. P. M.,	Jal, N.	Mex	Oil Field				County,
The method used in placing the cement was as follows: Halliburton Plug method Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: The Toxas Company Additional information: 1400f Pressure applied and allowed to stand for one hour- Except as follows: 19 Sincerely yours. Except as follows: Position Law Low Low Position Law Low Low Low Position Law Low Low Low Low Low Low Low Low Low Lo	on Dec. 20th	19.	4 . 36	lb. casing	was	cemented	in Anh	ydrite
The method used in placing the cement was as follows: Halliburton Plug method Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: The Toxas Company Additional information: 1400f Pressure applied and allowed to stand for one hour. Except as follows: 19 Sincepely yours. Except as follows: Position Universal of the place	formation at a dep	oth of	1607	feet on	Dec	ember 15th	···•	1954
Fluid level will be bailed to a depth of feet and left undisturbed for at least 12 hours before your inspection. Adjacent property owners have been notified as follows: The Toxas Company Additional information: 14004 Pressure applied and allowed to stand for one hours Except as follows: Sincerely yours. Except as follows: Position Leave Company or Operator. By Anglehamer Company or Operator. By Anglehamer Company or Operator.								
Fluid level will be bailed to a depth of	The method u	sed in placi	ing the cement	was as follov	vs:			
Additional information: 1400f Pressure applied and allowed to stand for one houre Approved Except as follows: 19 Sincerely yours. Company or Operator. By Anderson Company or Operator. Position Level.		_						
Additional information: 1400f Pressure applied and allowed to stand for one houre Approved Except as follows: 19 Sincerely yours. Company or Operator. By Anderson Company or Operator. Position Level.								
Additional information: 1400f Pressure applied and allowed to stand for one houre Approved 19 Sincerely yours. Except as follows: Out Company or Operator. By Association Care.	12 hours before yo	our inspection	on.					
Approved 19 Sincerely yours. Except as follows: By A. Jehman C. Position Dur.	Adjacent prop	erty owner	s have been not	ified as follo)ws:	The Bexas	Company	
Except as follows: By Jessel Position Un.	.		and allowed	to stand for	r one h	our•		
Except as follows: By Jessel Position Un.	Approved		19	Sincerely	yours.			
By A. Selmin Company or Operator. Position Que Long				Lin	no	al	60	
1 05101011				-			Company or	Operator.
Send communication regarding, well to Name In Set Surveyor 10				Position	10 m	, L.	/ -	
Name In Jahrele			/	Send com	municat	ion regarding	well to	
Illing 10 1 1 1 1 100			11/	Nama	2 10	Lane	eler	
State Goldstate Oil and Gas Inspector.		1/1	My	Address	Q,ce	uer V	micl	leend