

NOV 1961

(SUBMIT IN TRIPLICATE)

Land Office Las CrucesLease No. 032339 (a)

Unit _____

E. W. STANDLEY
DISTRICT ENGINEERUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	X	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR		WELL HISTORY	
NOTICE OF INTENTION TO ABANDON			

(INDICATE, OR OTHER DATA)

ILLEGIBLE

MATTIX NO. 5 _____, 1961
 Well No. 5 is located 1969.5 ft. from N line and 655.8 ft. from E line of sec. 3
S 4 W 4 Sec. 3 (Range) 24-S (Meridian) 107N
Langlie Mattix (Field) (County or Subdivision) Lea (State or Territory) New Mexico
 The elevation of the derrick floor above sea level is 3269 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill well with rotary tools at the above location to a depth of approximately 3,700 feet, unless commercial production is encountered at a lesser depth. All casing will be cemented in accordance with methods approved by the United States Geological Survey and any other special requirements will be complied with. The following casing pattern will be used:

9-5/8" casing will be set at approximately 300 feet, cemented with 300 sacks.
 7" CD casing will be set at approximately 3,400 feet, cemented with 150% of the volume of cement required to bring the cement above the base of the salt.

If the cement behind the 7" casing should circulate, no temperature survey will be run. If the cement does not circulate, a temperature survey will be run and if necessary the 7" casing will be perforated and recemented to bring the top of the cement above the base of the salt.

Company _____

Address CARTER FOUNDATION PRODUCTION COMPANYP. O. BOX 1688KEIGHT, TEXAS

By _____

Title ROY L. CARTER
FIELD MANAGER

APPROVED

188

APPROVED
188

APPROVED