

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYLand Office Las CrucesLease No. 032339 (a)

Unit \_\_\_\_\_

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

MATTIX No. 3

January 16, 1952

Well No. 3 is located 1981 ft. from NW line and 1977 ft. from W line of sec. 3NW/4 SE/4 Sec. 3  
(1/4 Sec. and Sec. No.)24-S  
(Twp.)37-E  
(Range)NMPM  
(Meridian)Langlie-Mattix  
(Field)Lea County  
(County or Subdivision)New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with cable tools at the above location to an approximate depth of 3,700 feet, unless commercial production is encountered at a lesser depth. All casing will be cemented in accordance with methods approved by the United States Geological Survey and any other special requirements will be complied with. The following casing pattern will be used:

13-3/8" OD casing will be set at approximately 300 feet and cemented with 175 sacks. 7" OD casing will be set at approximately 3,300 feet and cemented with 150% of volume required to bring cement to 200 feet above top of salt. If cement behind the 7" casing circulates, no temperature survey will be run. If cement does not circulate, a temperature survey will be run and if necessary the 7" casing will be perforated and recemented to bring top of cement at least 200 feet above top of salt.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Carter Foundation Production CompanyAddress P. O. Box 1688Kermit, TexasBy Ray E. Carter  
Title Field Manager