

VI.

WELLS WITHIN AREA OF REVIEW (1/2 MILE RADIUS)

Operator, Lease & Well No.	Location		Type	Date		Depth		Zone	Record of Completion
	Unit	Section Township Range		Spudded	Completed	TD	PBTD		
Getty Oil Company Myers-Langlie Mattix Unit Well #117	M	34 23-S 27-E 660' FS&WL's	Water Injector Converted: 8-22-78	Unknown	1-21-41	3571'	DD to 3700'	Queen	Open Hole: 3435'-3571' Casing: 13-3/8"@336'/250 sx, 9-5/8"@2550'/500 sx, 7"@3435'/100 sx, 4-1/2" Liner 3029'-3700'/125 sx Perfs: 3439'-3564', acid/3,000 gals
	N	34 23-S 37-E 660' FSL & 1980' FWL	Oil Producer	11- 8-50	12- 9-50	3578'		Queen	Open Hole: 3308'-3578' Casing: 10-3/4"@285'/150 sx, 5-1/2"@3308'/400 sx Treatment: Shot/400 qts. nitro
Well #123	B	3 24-S 37-E 660' FNL & 1980' FEL	Oil Producer	9-22-50	10-22-50	3564'		Queen	Open Hole: 3321'-3564' Casing: 10-3/4"@254'/150 sx, 7" @ 3321'/800 sx Treatment: Shot/470 qts. nitro
Well #126	A	4 24-S 37-E 660' FN&EL's	Water Injector	10-14-81	12- 1-81	3675'	3642'	Queen	Perfs: 3387'-3637' Casing: 8-5/8"@501'/350 sx, 5-1/2" @ 3671'/1000 sx Tubing: 2-3/8" @ 3318' Treatment: Acid/2,000 gals, Frac/ 21,000 gals & 6,000# sd
Well #152	G	3 24-S 37-E 1974' FNL & 1984' FEL	Water Injector (Inactive)	10- 7-51	11-26-51	3560'		Queen	Open Hole: 3328'-3560' Casing: 7" @ 3328'/800 sx Treatment: Shot/450 qts nitro
Well #149	H	4 24-S 37-E 1980' FNL & 660' FEL	Oil Producer	Unknown		3701'		Queen	Open Hole: 3459'-3665' Casing: 12-1/2" @201'/150 sx 8-5/8"@1250'/300 sx, 7"@3459'/100 sx
Well #162	L	3 24-S 37-E 1980' FSL & 560' FWL	Oil Producer	7-23-81	2-23-82	3745'	3697'	Queen	Perfs: 3460'-3619' Casing: 8-5/8"@501'/350 sx, 5-1/2"@3745'/1,100 sx Treatment: Acid/6,500 gals, Frac/33,000 gals & 60,000# sd

VI.

WELLS WITHIN AREA OF REVIEW (1/2 MILE RADIUS)

Operator, Lease & Well No.	Location		Type	Date		Depth		Zone	Record of Completion
	Unit	Section Township Range		Spudded	Completed	TD	PBTD		
Getty Oil Company Myers Langlie-Mattix Unit Well #163	I	4 24-S 37-E 1980' FSL & 660' FEL	Water Injector Converted:	Unknown	8-19-37	3640' DD 3731'		Queen	Open Hole: 3466'-3640' Casing: 12-1/2"@18", 8-5/8"@1374' / 400 sx, 5-1/2"@3466'/400 sx, Liner 3218'-3731'/125 sx Perfs: 3515'-3643', Acid/3,000 gals
	M	3 24-S 37-E 660' FS&WL's	Water Injector	7-11-81	3-15-82	3705'	3652'	Queen	Perfs: 3489'-3635' Casing: 8-5/8" @ 500'/350 sx, 5-1/2"@ 3703'/1150 sx Treatment: Acid/2,000 gals
Well #185									
Well #159	I	3 24-S 37-E 1980' FSL & 660' FEL	Water Injector (Inactive)	2- 6-52	3-19-52	3586'		Queen	Open Hole: 3323'-3586' Casing: 10-3/4" @ 261'/150 sx, 7" @ 3323'/800 sx
Well #188	P	3 24-S 37-E 660' FS&EL's	Oil Producer	8-16-78	9-15-78	3747'	3706'	Queen	Perfs: 3504'-3602' Casing: 8-5/8" @ 507'/275 sx, 5-1/2" @ 3746'/800 sx Treatment: Acid/2,000 gals, Frac/19,000 gals & 24,000# sd
Well #191	B	10 24-S 37-E 660' FNL & 1980' FEL	Oil Producer	12- 6-52	2-20-53	3643'	3635'	Queen	Open Hole: 3334'-3635' Casing: 9-5/8" @ 252'/165 sx, 5-1/2"@ 3334'/800 sx Treatment: Shot/350 qts nitro
Well #192	C	10 24-S 37-E 560' FNL & 2080' FWL	Water Injector	2-25-53	4-17-53	3582'		Queen	Open Hole: 3347'-3582' Casing: 8-5/8" @ 250'/125 sx, 5-1/2"@ 3347'/800 sx Treatment: Shot/250 qts nitro
Carter Foundation Production Company									
Eva E. Blinebry Federal Well #2	O	34 23-S 37-E 660' FSL & 1995' FEL	Oil Producer	4- 3-50	5-16-50	3536'		Queen	Open Hole: 3309'-3536' Casing: 13-3/8" @ 311'/175 sx, 7" @ 3309'/850 sx

VI.

WELLS WITHIN AREA OF REVIEW (1/2 MILE RADIUS)

Operator, Lease & Well No.	Location		Type	Date		Depth		Zone	Record of Completion
	Unit	Section Township Range		Spudded	Completed	TD	PBTD		
Carter Foundation Production Company									
G. H. Mattix Federal Well #7	K	3 24-S 1980' FS&WL's	37-E Oil Producer	10- 8-81	11-13-81	3730'	3722'	Queen	Perfs: 3474'-3638'
									Casing: 8-5/8" @ 507'/360 sx, 5-1/2" @ 3722'/900 sx
									Tubing: 2-3/8" @ 3638'
									Treatment: Acid/6,000 gals, Frac/36,000 gals & 72,000# sd
Well #8	N	3 24-S 660' FSL & 1980' FWL	37-E Oil Producer	8- 1-81	9-21-81	3692'		Queen	Perfs: 3475'-3626'
									Casing: 8-5/8" @ 565'/360 sx 5-1/2" @ 3692'/900 sx
									Tubing: 2-3/8" @ 3579'
									Treatment: Acid/5,000 gals, Frac/36,000 gals, 10/20 & 10/40 sd
Pearson-Sibert Oil Co. of Texas									
G. H. Mattix Federal Well #1	A	10 24-S 660' FN&EL's	37-E Oil Producer	5-29-52	7- 2-52	3621'		Queen	Open Hole: 3435'-3621'
									Casing: 9-5/8" @ 326'/250 sx 5-1/2" @ 3435'/400 sx
									Tubing: 2-3/8" @ 3612'