

NEW MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plugging and Abandoning	XX

April 10, 1952

Hobbs, New Mexico

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the.....

Gulf Oil Corporation S. J. Carr Well No. 1 in the
Company or Operator Lease
NW SW of Sec. 3, T. 24S, R. 37E, N. M. P. M.,
Langlie-Mattix Pool Lea County.

The dates of this work were as follows: Completed 4-8-52

Notice of intention to do the work was ~~received~~ submitted on Form C-102 on March 13, 1952,
and approval of the proposed plan was ~~received~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD 3886'. PBTD 3625'. 15-1/2" casing set at 148', not cemented. 12-1/2" casing set at 362', not cemented. 10-3/4" casing set at 1237', cement circulated. 7" casing set at 3484', top cement at 3440'.

PLUGGING PROCEDURE

1. Filled hole full of heavy mud.
2. Set Baker Model K cement retainer at 3466' and squeeze cemented below with 20 sacks cement. Maximum pressure 1800#. Backwashed 3 sacks cement. 15' above retainer.
3. Shot 7" casing off at 2554' and pulled same.
4. Spotted cement plug from 2520' to 2445'. 34 sacks cement.
5. Placed bridge in 10-3/4" casing at 25' and filled casing from 25' to surface with 13 sacks cement. Set 4" marker extending 4' above ground level.

Witnessed by Mr. J. R. Tate Gulf Oil Corporation Prod. Foreman
Name Company Title

APPROVED:
OIL CONSERVATION COMMISSION

Ray Yankovich
Name
Oil & Gas Inspector Title

Date

19

I hereby swear or affirm that the information given above is true and correct.

Name CO Borland
Position Asst Area Prod. Supt.
Representing Gulf Oil Corporation
Company or Operator
Address Box 2167, Hobbs, New Mexico