

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		Plug and Abandon Well	XX

Hobbs, New Mexico

March 13, 1952

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Gulf Oil Corporation S. J. Carr Well No. 1 in NW SW
Company or Operator Lease
of Sec. 3, T. 24S, R. 37E, N. M. P. M., Langlie-Mattix Field.
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

TD 3886'. PBD 3625'. 15-1/2" casing set at 148', not cemented. 12-1/2" casing set at 362', not cemented. 10-3/4" casing set at 1237', cement circulated. 7" casing set at 3484', top of cement at 2500'.

PROPOSED PLUGGING PROCEDURE

1. Fill hole full of mud.
2. Set Baker Model k cement retainer in 7" casing at 3470' and plug back below retainer from 3625' to 3470'. 40 sacks cement.
3. Shoot off 7" casing at approximately 2500'.
4. Pull 2500' of 7" casing.
5. Place cement plug from 2525' to 2500'. 10 sacks cement.
6. Plug back from 2500' to 2450'. 24 sacks cement.
7. Place bridge 25' down inside 10-3/4" casing.
8. Fill top 25' of 10-3/4" casing with cement. 13 sacks cement.
9. Surface cement plug. 5 sacks cement.
10. Place 4" pipe marker inside 10-3/4" casing and extend 4' above mean ground level.

Approved MAR 17 1952, 19_____
except at follows:

Gulf Oil Corporation

Company or Operator

By E. H. TaylorPosition Area Prod. Supt.

Send communications regarding well to

Name Gulf Oil CorporationAddress Box 2167, Hobbs, New Mexico

OIL CONSERVATION COMMISSION

By Ray Garbrough

Title _____