



# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	60	60	Caliche
60	190	130	Red Sand
190	305	115	Red Rock
305	410	105	Red Rock & Shale
410	615	205	Red Rock
615	675	60	Water Sand
675	735	60	Red Rock & Sand
735	1095	360	Red Rock
1095	1190	95	Anhydrite
1190	1230	40	Red Rock & Anhydrite
1230	1250	20	Anhydrite
1250	1380	130	Salt
1380	1415	35	Anhydrite & Salt
1415	1640	225	Salt
1640	1760	120	Salt & Potash
1760	2095	335	Salt
2095	2340	245	Lime.
2340	2425	85	Lime & Anhydrite
2425	2705	280	Hard Lime
2705	3080	375	Gray & White Lime
3080	3170	90	Gray lime
3170	3240	70	Hard White Lime
3240	3255	15	Hard Brown Lime
3255	3430	175	Hard White Lime
3430	3457	27	Gray Sandy Lime
3457	3510	53	Hard Gray Lime
3510	3568	58	Lime & Sandy Lime
3568	3590	22 22	Soft Sand
3590	3594	4	Gray Lime
3594	3605	11	White Lime
	#		
	3605		

TOTAL DEPTH

Deviation Test Results as Follows:

500' - 10'	2500' - 0°
1000' - 1-7/8°	2900' - 1/8°
1600' - 1°	3330' - 5/8°
2000' - 1°	