

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other) Sand Frac Treat	X

August 24, 1954

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation

(Company or Operator)

Carter-Haves

(Lease)

Dowell

(Contractor)

Well No. 3 in the SE SW 1/4 of Sec. 6T. 24-S, R. 37-E, NMPM, Langlie-Mattix Pool, Lee County.The Dates of this work were as follows: August 20-22, 1954Notice of intention to do the work (~~was~~) (was not) submitted on Form C-102 on _____, 19____,

(Cross out incorrect words)

and approval of the proposed plan (~~was~~) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 2-7/8" tubing with straddle packers at 3530' and 3455'. Pumped 27 bbls oil ahead of sand frac. Treated thru tubing below bottom packer from 3530' to 3575' with 5000 gallons sand frac with 1# sand per gallon. Flushed with 97 bbls oil. Tubing pressure 3800-3000#. Pumped 22 bbls oil ahead of sand frac. Treated thru tubing between packers 3455' to 3530' with 3000 gallons sand frac with 1# sand per gallon. Flushed with 130 bbls oil. Tubing pressure 3000-2000#. Casing pressure 400# packer pressure applied.

Swabbed 49 bbls load oil, no water thru 2-3/8" tubing in 2 hours. Well kicked off. Flowed 77 bbls load oil, no water 24 hours. Flowed 58 bbls load oil, 2 bbls water 25 hours.

Witnessed by C. C. Brown Gulf Oil Corporation Field Foreman
(Name) (Company) (Title)

Approved: S. J. Stanley
OIL CONSERVATION COMMISSION
(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name S. J. Stanley

Position Asst. Area Supt. of Prod.

Representing Gulf Oil Corporation

Address Box 2167, Hobbs, New Mexico

Engineer District I AUG 27 1954
(Title) (Date)