

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

1954 APR 27 AM 10:14

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 26, 1954
(Date)Hobbs, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation
(Company or Operator)Carter-Byes
(Lease)DPL Company
(Contractor)

Well No. 3 in the SE 1/4 SW 1/4 of Sec. 6

T. 24-S, R. 37-E, NMPM., Langlie-Mattix Pool, Lea County.

The Dates of this work were as follows: April 23-25, 1954

Notice of intention to do the work ☒ (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)and approval of the proposed plan ☒ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 115 jts (3407') of 7" 20# J-55 Electric Weld Casing w/3 centralizers and 12 scratchers from 3419-3269'. Set and cemented at 3419' w/525 sacks cement in two stages. 1st stage w/150 sacks 4% Gel and 100 sacks neat on bottom. 2nd stage thru DV tool w/225 sacks 4% Gel and 50 sacks neat at DV tool. Circulated approx. 3 sacks cement. DV tool set at 1081'.

After waiting over 36 hours, tested 7" casing w/1000# for 30 minutes. There was no drop in pressure. Drilled DV tool at 1081' and tested DV tool w/1500# for 30 minutes. There was no drop in pressure. Drilled cement from 3359-3419' and tested cement below casing shoe w/1000# for 30 minutes. There was no drop in pressure.

Witnessed by Glenn Stach
(Name)Gulf Oil Corporation
(Company)Drig. Foreman
(Title)

Approved:

OIL CONSERVATION COMMISSION

S. J. Stanley
(Name)

Engr.

(Title)

APR 28 1954

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

Position

Representing

Address

Area Prod. Supt.

Gulf Oil Corp.

Box 2167, Hobbs, N.M.