

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Sinclair Oil & Gas Company	8. Farm or Lease Name Jim Camp WN
3. Address of Operator Box 1920, Hobbs, New Mexico, 88240	9. Well No. 2
4. Location of Well UNIT LETTER E 1980 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 6 TOWNSHIP 24S RANGE 37E NMPM.	10. Field and Pool, or Wildcat Jalmat
15. Elevation (Show whether DF, RT, GR, etc.) 3317' GR	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☐

OTHER **Set BP, Perf., Test & Treat Jalmat Gas** ☒


ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 3-27-65** Set CI bridge plug at 3380'. Spotted 2 sacks cement 3380-62'. Ran Walex Bond Log 2600-3356.
- 3-28-65** Jet perforate Jalmat 2944, 2950, 2957, 2973, 2986, 2994, 3004, 3018, 3026, 3045, 3060, 3067, 3072, 3137, 3142, 3154, 3167, 3172, 3180, 3222, 3230 and 3234'. Acidized perforations 3137-3234 with 1500 gal. acid and 22 RCN ball sealers, max. press 2200#, min. 1000#.
- 3-30-65** Acidized Jalmat perforations 2944-3072' with 1500 gal. acid and 32 7/8" RCN ball sealers. Max. press 2400#, min. 2000#.
- 4-2-65** Sand-oil fraced Jalmat perforations 2944-3234' with 20,000 gal. ref. oil 20,000# sand and 48 ball sealers. Max press. 4100#, min. 4000#.
- 4-6-65** Flowed Jalmat perforations 2944-3234 1212 MCF gas in 24 hrs. on 20/64" choke. Tubing pressure 250#.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED  TITLE **Superintendent** DATE **4-12-65**

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: