NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	-	NOTICE OF INTE	NTION TO SHOOT	OR
	XX	CHEMICALLY	TREAT WELL NTION TO PULL OF	1
NOTICE OF INTENTION TO CHANGE PLANS		OTHERWISE	ALTER CASING	£
NOTICE OF INTENTION TO REPAIR WELL	_	NOTICE OF INTE	NTION TO PLUG W	ELL
NOTICE OF INTENTION TO DEEPEN WELL				
Hobbs, New Mo	exico		Nov. 26, 19)LB
OIL GONGWINI MYON GONGREGATOR		Place	Date	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico.				
Gentlemen:				
Following is a notice of intention to do certain we	ork as de	escribed below at the		
Skelly Oil Company	Liber	ty-Royalties		in SE/4 NW/4 SE
	ease			
of Sec, T24_S, R37	<u>r</u> , 1	I. M. P. M., Lan	glie-Mattiw	Field.
Lea County.				
FULL DETAILS OF	TOTAL	OCED DI AN OF		
FOLLOW INSTRUCTIONS IN THE R	IUMI	VD DEGULATION	WORK	
		ND REGULATIONS	OF THE COMMISS	SION
Drilled to T.D. 1192', ran a at 1192' with 400 sacks of c Halliburton Process used. W	ement.	Cement circula	10-3/4" OD cast	rface.
Drilled to T.D. 1192', ran a at 1192' with 400 sacks of e Halliburton Process used. Wat approximately 7:00 A.M. w	ement.	Cement circula	10-3/4" OD cast	rface.
Halliburton Process used. W	ement.	Cement circula	10-3/4" OD cast	rface.
Halliburton Process used. W	ement.	Cement circula	10-3/4" OD cast	rface.
Halliburton Process used. W	ement.	Cement circula	10-3/4" OD cast	rface.
Halliburton Process used. We at approximately 7:00 A.M. w	ement.	cement circula t set 48 hours a fill plug and tes	10-3/4" OD cast	rface.
Halliburton Process used. Wat approximately 7:00 A.M. w	ement.	Skelly O	10-3/4" OD cast ated back to sur and on November at casing shut-o	rface.
Halliburton Process used. Wat approximately 7:00 A.M. w	ement.	Skelly 0	10-3/4" OD cast ated back to sur and on November st casing shut-o il Company mpany or Operator	rface.
Halliburton Process used. Wat approximately 7:00 A.M. w	ement.	Skelly O	10-3/4" OD casinted back to sure and on November st casing shut-of the	rface.
Halliburton Process used. Wat approximately 7:00 A.M. w	ement.	Skelly O	il Company mpany or Operator Supt.	rface. 27, 1948 off.
Halliburton Process used. Wat approximately 7:00 A.M. w	ement.	Skelly O Skelly O Son By Position Send communications Send communications Position Send communications Position Send communications Send communications Position Send communications Sen	il Company mpany or Operator Supt. inted back to sur and on November st casing shut-of the Company mpany or Operator surface supt.	rface. 27, 1948 off.
Halliburton Process used. Wat approximately 7:00 A.M. w	ement.	Skelly O Skelly O Son By Position Send communications Send communications Position Send communications Position Send communications Send communications Position Send communications Sen	il Company mpany or Operator Supt.	rface. 27, 1948 off.
Halliburton Process used. Wat approximately 7:00 A.M. w	ement.	Skelly O	il Company mications regarding voil Company Oil Company	rface. 27, 1948 off.