

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

November 12, 1948

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Skelly Oil Company

Liberty-Royalties

Well No. 5

in CSR 1/4 NW 1/4 SE 1/4

Company or Operator

Lease

of Sec. 7, T. 24S, R. 37E, N. M., P. M., Langlie-Mattix Field, Lea County.

N

The well is 1650 feet (N.) (S.) of the South line and 1650 feet (E.) (W.) of the East line of Section 7

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. Assignment No.

If patented land the owner is Liberty-Royalties Corp.


Address Tulsa, Oklahoma

If government land the permittee is

Address

The lessee is Skelly Oil Company

Address Tulsa, Oklahoma



AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: Rotary Tools

from top to total depth.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
12-1/2"	9-5/8"	36#	New	1200'	Cemented	400 sacks
7-7/8"	5-1/2"	17#	New	3300'	"	300 "

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 2870 feet.

Additional information:

Halliburton Process will be used in cementing all casing.

Approved \_\_\_\_\_, 19\_\_\_\_  
except as follows: NOV 15 1948

Sincerely yours,

Skelly Oil Company

Company or Operator

By

Dist. Supt.

Position

Send communications regarding well to

Name Skelly Oil Company

Address Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Title

By Roy Garbrough  
Title INSPECTOR