

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

APR 28 1949
RECEIVED
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

April 26, 1949

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Cities Service Oil Company **Hodges** Well No. 1 in the _____

Company or Operator A Lease 24S of Sec. 8, T. 24S, R. 37E, N. M. P. M.,
Langlie-Mattix Field, Lea County.

The dates of this work were as follows: April 26, 1949

Notice of intention to do the work was (~~was~~/~~not~~) submitted on Form C-102 on April 20 19 49
 and approval of the proposed plan was (~~was~~/~~not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well was originally drilled to a total depth of 3575' with 39' 11" of 12 1/2" casing cemented with 50 sacks; set 7 5/8" casing at 1300' and cemented with 300 sacks; and set 5 1/2" casing at 3420' and cemented with 160 sacks. This well has had remedial work done but production declined until it was no longer productive. Further remedial work is deemed in-advisable.

The hole was loaded with mud; 40 sacks of cement were spotted in open hole and into 5 1/2" casing; run 40 sacks of cement at 1350'; run 30 sacks of cement at 900' and 10 sacks of cement in top of 8 5/8" leaving a 4" - 4" marker bull-plugged at old location.

Witnessed by R. W. Ely Cities Service Oil Company Dist. Supt.

Name	Company	Title

Subscribed and sworn before me this _____

27th day of April 19 49

[Signature]
 Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name [Signature]

Position District Superintendent

Representing Cities Service Oil Company
 Company or Operator

My commission expires March 12, 1951

Address Drawer G., Hobbs, New Mexico

Remarks:

APPROVED

Date APR 28 1949

[Signature]
 Name
 Title

30-025-11054