



AREA 640 ACRES  
LOCATE WELL CORRECTLY

OBP-1 NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

Olsen-Blount Oil Company  
(Company or Operator)  
Hodge  
(Lease)  
Well No. 3, in C NW 1/4 of NE 1/4, of Sec. 8, T. 24S, R. 37E, NMPM.  
Langlie-Mattix Pool, Lea County.  
Well is 660 feet from North line and 1980 feet from East line  
of Section 8-24S-37E. If State Land the Oil and Gas Lease No. is  
Drilling Commenced August 23, 1954. Drilling was Completed September 12, 1954.  
Name of Drilling Contractor Olsen-Blount Oil Co.  
Address Oklahoma City, Oklahoma  
Elevation above sea level at Top of Tubing Head 3286'. The information given is to be kept confidential until  
19

OIL SANDS OR ZONES

No. 1, from 3450' to 3561' No. 4, from  
No. 2, from to No. 5, from to  
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.  
No. 2, from to feet.  
No. 3, from to feet.  
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8	23#	New	279.50	HowCo.			Surface casing
5-1/2"	15.50#	New	3383'	HowCo.			String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	8-5/8"	286'	225	Halliburton		
	5-1/2"	3390'	300	Halliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Sandfraced 3398 to 3561 with 10,000 Gallons and 10,000# sand.

of Production Stimulation 45 Barrels oil per Hr.

Depth Cleaned Out

# RD OF DRILL-STEM AND SPECIAL TEST

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

## TOOLS USED

Rotary tools were used from 0' feet to 3561' feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

## PRODUCTION

Put to Producing September 12, 1954

OIL WELL: The production during the first 24 hours was 45 barrels of liquid of which 100% was  
was oil; % was emulsion; % water; and % was sediment. A.P.I.  
Gravity 37

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of  
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

### Southeastern New Mexico

### Northwestern New Mexico

T. Anhy. 1145'	T. Devonian	T. Ojo Alamo
T. Salt. 1300'	T. Silurian	T. Kirtland-Fruitland
B. Salt. 2600'	T. Montoya	T. Farmington
T. Yates. 2900'	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen. 3450'	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

## FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
1145'	1300'		Anhydrite				
1300'	2600'		Salt				
2600'	2675'		Anhydrite				
2675'	2900'		Line				
2900'	3075'		Sand				
3075'	3385'		Dolomite				
3385'	3450'		Dolomite with sand stringers				
3450'	3561'		Sand				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

September 29, 1954 (Date)  
Company or Operator Olson-Blount Oil Co. Address Drawer 4, Jal, New Mexico  
Name Johnnie French Position or Title Superintendent