## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is comresult of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional

	Indicate Nature of Report by Checking Be	low
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)
	October 19, 1954	Jal, New Mexico
Following is a report on the work	done and the results obtained under the heading ne	oted above at the
R. Olsen (Company or Ope	erator)	Hadge
Olsen-Blount Dril	ling Co.	(Lease)
(Contractor	ling Co. Well No. 4	in the SW
, N. 272, NMPM.,La	nglie-Mattix Pool,	Lea
he Dates of this work were as follows:	10/12 and 10/14	·
otice of intention to do the work (1/1)	,	
to do the work (was)	(was not) submitted on Form C-102 on	7000 001 10
nd approval of the proposed plan (was)	(was not) obtained.	ross out incorrect words)
Drillad	ED ACCOUNT OF WORK DONE AND RESULT	
Drilled casing set at 3400 100 sacks thru 2-S	to a total depth of 3404. Ran 300 using 300 sacks of cement. 200 tage tool set at 1100. Plug down	393' of $5-\frac{1}{2}$ " 15.5# sacks at shoe and at 8 P.M. 10/12.
Drilled casing set at 3400 100 sacks thru 2-S	to a total depth of 3404. Ran 300 using 300 sacks of cement. 200 tage tool set at 1100. Plug down	393' of $5-\frac{1}{2}$ " 15.5# sacks at shoe and at 8 P.M. 10/12.
Drilled casing set at 3400 100 sacks thru 2-S	to a total depth of 3404. Ran 320 using 300 sacks of cement. 200 stage tool set at 1100. Plug down dup with 1000# pressure and held Shut off okay. Started drilling	393' of 5-2" 15.5# sacks at shoe and at 8 P.M. 10/12.  for 30 minutes. No cement at 8 P.M.
Drilled casing set at 3400 100 sacks thru 2-S  Pressure loss in pressure. 10/14/54.	to a total depth of 3404. Ran 300 using 300 sacks of cement. 200 tage tool set at 1100. Plug down	393' of 5-1" 15.5# sacks at shoe and at 8 P.M. 10/12.  for 30 minutes. No cement at 8 P.M.
Drilled casing set at 3400 100 sacks thru 2-S  Pressure loss in pressure. 10/14/54.  thessed by Ladell Ellis (Name)	to a total depth of 3404. Ran 320 using 300 sacks of cement. 200 stage tool set at 1100. Plug down dup with 1000# pressure and held Shut off okay. Started drilling	393' of 5-1" 15.5# sacks at shoe and at 8 P.M. 10/12.  for 30 minutes. No cement at 8 P.M.
Drilled casing set at 3400 100 sacks thru 2-S  Pressure loss in pressure. 10/14/54.	to a total depth of 3404. Ran 320 using 300 sacks of cement. 200 stage tool set at 1100. Plug down dup with 1000# pressure and held Shut off okay. Started drilling  Olsen-Blount Drilling Company  I hereby certify that the to the best of my know Name.	sacks at shoe and at 8 P.M. 10/12.  for 30 minutes. No cement at 8 P.M.  Tool Pusher.  (Title)  information given above is true and complete ledge.
Drilled casing set at 3400 100 sacks thru 2-S  Pressure loss in pressure. 10/14/54.  nessed by Ladell Ellis (Name) roved:	to a total depth of 3404. Ran 320 using 300 sacks of cement. 200 stage tool set at 1100. Plug down dup with 1000# pressure and held Shut off okay. Started drilling  Olsen-Blount Drilling Company  I hereby certify that the to the best of my know Name.	sacks at shoe and at 8 P.M. 10/12.  for 30 minutes. No cement at 8 P.M.  Tool Pusher  (Title)  reinformation given above is true and complete ledge.