

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN OR
(Other instructions
verse side)

COPY TO O. C. C.

Field Office No.
District Office No.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT EQUIPMENT NO.

8. IF INDIAN, ADOPTED NAME

7. UNIT EQUIPMENT NO.

8. IF INDIAN, ADOPTED NAME

9. WELL NO.

10. FIELD AND POOL, OR WELL NO.

11. SEC., T., R., OR BLK. AND
SURVEY OR AREA

12. COUNTY OR PARISH

13. STATE

1. OIL ☐ GAS ☐ OTHER ☒ *Salt Water Disposal Well*

2. NAME OF OPERATOR
PAN AMERICAN PETROLEUM CORPORATION

NAME CHANGED:
FROM: PAN AMERICAN PETR. CORP.
TO: AMOCO PRODUCTION CO.

3. ADDRESS OF OPERATOR
BOX 68, HOSBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with State requirements.
See also space 17 below.)
At surface

1650' FSL x 660' FEL 3029 (Unit I, 11/19/68)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3293' R.D.B.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) *Well Completion*

(Other)

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Well Completion accomplished as follows:
Spotted 25 sq. cement plug 5800-5550. (5136-5610')
Shot 5 1/2" casing @ 5136, 4922, 4723, 4593, 4317, 3943' + pulled.
Spotted 30 sq cement plug 5000' - 4600'.
Perforated intervals 4170-4144, 4128-92, 4255-60,
4293-4302, 4340-44 w/ 21SPF.

Get Baker Model N Packer @ 3305 and run
2 3/4" OD Plastic Coated Tubing.

TD-7996'

700-4593'

Comp - 10-15-68

18. I hereby certify that the foregoing is true and correct

SIGNED

James E. Smith

TITLE

Area Eng

DATE

11-19-68

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

067-UGS-N
1-NSUB
1-500P
1-1224

*See Instructions on Reverse Side

NOV 22 1968

J. L. GORDON
ACTING DISTRICT ENGINEER