

NO. OF COPIES RECEIVED	
DISTRIBUTION	
NTA FE	
LE	
S.G.S.	
AND OFFICE	
PERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

<p>SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR APPLICATIONS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)</p>		<p>5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/></p>
<p>Oil <input checked="" type="checkbox"/> Gas <input type="checkbox"/> Other <input type="checkbox"/></p>		<p>5. State Oil & Gas Lease No.</p>
<p>Name of Operator Gulf Oil Corporation</p>		<p>7. Unit Agreement Name</p>
<p>Address of Operator P. O. Box 670, Hobbs, NM 88240</p>		<p>8. Farm or Lease Name S. J. Carr</p>
<p>Location of Well UNIT LETTER N -550 FEET FROM THE south LINE AND -2080 FEET FROM THE west LINE, SECTION 10 TOWNSHIP 24-S RANGE 37-E NMPM.</p>		<p>9. Well No. 5</p>
<p>10. Field and Pool, or Wildcat Fowler Upper Yeso</p>		
<p>11. Elevation (Show whether DF, RT, GR, etc.) 3252' GL</p>		<p>12. County Lea</p>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
<p>REPAIR REMEDIAL WORK <input type="checkbox"/></p> <p>IMPROVEMENT ABANDON <input type="checkbox"/></p> <p>RECEMENT SURFACE PIPE <input type="checkbox"/></p>	<p>PLUG AND ABANDON <input type="checkbox"/></p> <p>CHANGE PLANS <input type="checkbox"/></p>	<p>REMEDIAL WORK <input type="checkbox"/></p> <p>COMMENCE DRILLING OPS. <input type="checkbox"/></p> <p>CASING TEST AND CEMENT JOB <input type="checkbox"/></p> <p>OTHER <input type="checkbox"/></p>	<p>ALTERING CASING <input type="checkbox"/></p> <p>PLUG AND ABANDONMENT <input type="checkbox"/></p>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5790' PB.

Pump down 9-5/8" casing x 13-3/8" annulus with 200 sacks Class C cement with 3# salt and 2% CaCl₂ to eliminate pressure on surface casing head.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

<p>SIGNED <u>D. F. Berlin</u></p>	<p>TITLE <u>Area Engineer</u></p>	<p>DATE <u>12-6-76</u></p>
<p>APPROVED BY _____</p>	<p>TITLE _____</p>	<p>DATE _____</p>

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

1975

U.S. DEPARTMENT OF COMMERCE
BUREAU OF ECONOMIC ANALYSIS
WASHINGTON, D. C.