

5-USGS-HOBBS

1-A.B. CARY-MIDLAND

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
reverse side)E
reForm approved.
Budget Bureau No. 42-R1424.

1-FILE

5. LEASE DESIGNATION AND SERIAL NO.

LC-032339 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

MYERS LANGLIE MATTIX UNIT

8. FARM OR LEASE NAME

250

9. WELL NO.

LANGLIE MATTIX

10. FIELD AND POOL, OR WILDCAT

SEC.10-24S-37E

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

12. COUNTY OR PARISH

LEA

13. STATE

N.MEX.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER

WATER INJECTION

2. NAME OF OPERATOR

GETTY OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. BOX 730, HOBBS, NEW MEXICO 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface660' FSL & 1980' FEL
SECTION 10

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3250 D.F.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

CONVERT TO WATER-INJ.

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*Ran 6-1/4" bit on 2-7/8" tubing. Washed out to 3537' T.D. Drilled new hole w/6-1/8"
bit to 3635' T.D. Set 2-3/8" plastic coated internally tubing at 3167', with Baker
AD-1 Tension Packer at 3163'.

Converted to WW 8-20-77

RECEIVED
OCT 17 1977
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

DALE CROCKETT

TITLE

AREA SUPERINTENDENT

DATE

10-14-77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

WLK/bh

*See Instructions on Reverse Side

ACCEPTED FOR RECORD
OCT 18 1977U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

APR 2 1977
OIL CONSERVATION COMPANY
HOBBS, N. M.