

N.

(Revised 7/1/52)
(Form C-105)

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

C. B. Day

(Company or Operator)

Sam Rahr

(Lease)

Well No. 1, in NE 1/4 of NW 1/4, of Sec. 11, T. 24S, R. 37E, NMPM.

Langley Martin

Pool, Lee

County.

Well is 660 feet from E line and 660 feet from W line

of Section 11. If State Land the Oil and Gas Lease No. is

Drilling Commenced 6-21, 1932. Drilling was Completed 7-22, 1932.

Name of Drilling Contractor: Gaskie Drilling Company

Address: Hobbs, New Mexico

Elevation above sea level at Top of Tubing Head 3233.9. The information given is to be kept confidential until

, 19

OIL SANDS OR ZONES

No. 1, from 3628 to 3642 Oil No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 3670' to 3681' feet. 700' sulphur water

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
10 3/4	32.75	New	225'	HW90			Surface
9 1/2	15.70	New	350'	HW90			Oil String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	10 3/4	225'	250	Pump		
7 7/8"	9 1/2	350'	400	Pump		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

3000 gallons of Stim-Frac, 1/4 pound of sand per gallon, acid with sweet packer set at 3610', treated 3610' to 3694'.

Result of Production Stimulation

ILLEGIBLE

Depth Cleaned Out

ED OF DRILL-STEM AND SPECIAL

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3700 feet, and from feet to feet.
Cable tools were used from 3700 feet to 3821 feet, and from feet to feet.

PRODUCTION

Put to Producing 8-4, 1932
OIL WELL: The production during the first 24 hours was 29 barrels of liquid of which 90% was oil; % was emulsion; 20% water; and % was sediment. A.P.I. Gravity.
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure 900 lbs.
Length of Time Shut in 24 hours

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico
T. Anhy.	T. Devonian.	T. Ojo Alamo.
T. Salt.	T. Silurian.	T. Kirtland-Fruitland.
B. Salt.	T. Montoya.	T. Farmington.
T. Yates.	T. Simpson.	T. Pictured Cliffs.
T. 7 Rivers.	T. McKee.	T. Menefee.
T. Queen.	T. Ellenburger.	T. Point Lookout.
T. Grayburg.	T. Gr. Wash.	T. Mancos.
T. San Andres.	T. Granite.	T. Dakota.
T. Glorieta.	T.	T. Morrison.
T. Drinkard.	T.	T. Penn.
T. Tubbs.	T.	T.
T. Abo.	T.	T.
T. Penn.	T.	T.
T. Miss.	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	125	125	Caliche and sand				
125	604	479	Red bed				
604	976	370	Red bed and sand				
976	1030	50	Red bed and shale				
1030	1123	93	Shale				
1123	2024	1909	Shale and salt				
2024	2339	315	Lime				
2339	2671	332	Lime Gyp.				
2671	3290	619	Lime Shale				
3290	3424	134	Lime Gyp.				
3424	3600	176	Lime and Dolomite				
3600	3620	20	Sandy shale				
3620	3635	15	Gray lime				
3635	3693	58	Sandy lime				
3693	3620	73	Gray lime				
3620	3642	22	Oil and Gas				
3642	3690	48	Green shale and gray lime				
3690	3681	9	Sulphur water and sand				

ILLEGIBLE

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator C. V. Day
Name D. W. Coffey
Address Box 216, Seminole, Texas
Position or Title Supt.