

FORMATION RECORD

| FROM | TO | THICKNESS IN FEET | FORMATION |
|------|-------------|----------------------|---|
| 0 | 15 | 15 | Caliche |
| 15 | 50 | 35 | Sand |
| 50 | 70 | 20 | Broken Lime |
| 70 | 80 | 10 | Red Bed |
| 80 | 130 | 50 | Red Shale |
| 130 | 295 | 165 | Red Bed |
| 295 | 315 | 20 | Gray Sandy Shale |
| 315 | 395 | 80 | Red Bed |
| 395 | 445 | 50 | Red Rock |
| 445 | 460 | 15 | Gray Shale |
| 460 | 495 | 35 | Sand - Water 485' |
| 495 | 525 | 30 | Red Shale |
| 525 | 570 | 45 | Sand |
| 570 | 580 | 10 | Red Rock |
| 580 | 870 | 290 | Red Bed - (Running 10" Casing) - Water 777' |
| 870 | 895 | 25 | Red Shale |
| 895 | 960 | 65 | Red Bed |
| 960 | 1125 | 165 | Anhydrite - water 1075' |
| 1125 | 1145 | 20 | Red Bed |
| 1145 | 1165 | 20 | Salt and Anhydrite |
| 1165 | 1190 | 25 | Red Bed and Anhydrite Shells |
| 1190 | 1205 | 15 | Red Bed |
| 1205 | 1220 | 15 | Anhydrite and Red Bed |
| 1220 | 1250 | 30 | Red Bed |
| 1250 | 1265 | 15 | Anhydrite and Potash |
| 1265 | 1275 | 10 | Anhydrite and Red Bed |
| 1275 | 1300 | 25 | Anhydrite, Salt and Red Rock |
| 1300 | | | Run 1295' of 8" Casing - Surface Shut-off, cementing with 50 sacks of cement- Pulled 10" Casing 777'. |
| 1300 | 1335 | 35 | Salt |
| 1335 | 1420 | 85 | Salt and Anhydrite |
| 1420 | 1600 | 180 | Salt and Potash |
| 1600 | 1650 | 50 | Salt and Anhydrite |
| 1650 | 1655 | 5 | Anhydrite |
| 1655 | 1680 | 25 | Salt |
| 1680 | 1695 | 15 | Anhydrite |
| 1695 | 1705 | 10 | Salt and Anhydrite, Potash |
| 1705 | 1745 | 40 | Salt and Anhydrite |
| 1745 | 1960 | 215 | Salt |
| 1960 | 2025 | 65 | Anhydrite |
| 2025 | 2055 | 30 | Salt |
| 2055 | 2065 | 10 | Anhydrite |
| 2065 | 2080 | 15 | Salt and Potash |
| 2080 | 2120 | 40 | Anhydrite |
| 2120 | 2155 | 35 | Salt and Anhydrite Shells |
| 2155 | 2160 | 5 | Anhydrite |
| 2160 | 2170 | 10 | Salt |
| 2170 | 2180 | 10 | Anhydrite |
| 2180 | 2195 | 15 | Salt |
| 2195 | 2200 | 5 | Anhydrite |
| 2200 | 2210 | 10 | Salt |
| 2210 | 2225 | 15 | Salt and Anhydrite |
| 2225 | 2270 | 45 | Anhydrite |
| 2270 | 2290 | 20 | Salt |
| 2290 | 2300 | 10 | Anhydrite |
| 2300 | 2400 | 100 | Salt |
| 2400 | 2410 | 10 | Anhydrite |
| 2410 | 2420 | 10 | Lime |
| 2420 | 2700 | 280 | Anhydrite |
| 2700 | 2705 | 5 | Lime |
| 2705 | 2915 | 210 | Anhydrite |
| 2915 | 2925 | 10 | Lime |
| 2925 | 2950 | 25 | Lime and Anhydrite |
| 2950 | 2975 | 25 | Anhydrite |
| 2975 | 3010 | 35 | Lime and Anhydrite |
| 3010 | 3020 | 10 | Anhydrite |
| 3020 | 3085 | 65 | Lime and Anhydrite |
| 3085 | 3105 | 20 | Lime |
| 3105 | 3210 | 105 | Anhydrite and Lime |
| 3210 | 3308 | 98 | Anhydrite Lime - Run 7" O.D. Casing 3313' Cemented with 100 sacks of cement |
| 3308 | 3313 | 5 | Brown hard Lime |
| 3313 | 3333 | 20 | Lime |
| 3333 | 3344 | 11 | Gray Lime |
| 3344 | 3375 | 31 | Lime |
| 3375 | 3389 | 14 | Gray Lime |
| 3389 | 3415 | 26 | Lime |
| 3415 | 3427 | 12 | Gray Sandy Lime |
| 3427 | 3459 | 32 | Lime |
| 3459 | 3464 | 5 | Sandy Lime |
| 3464 | 3492 | 28 | Lime - (Show of gas and oil-3482'-3489') |
| 3492 | 3500 | 8 | Gray Sandy Lime |
| 3500 | 3510 | 10 | Lime |
| 3510 | 3563 | 53 | Oil Sand (Increase of gas and oil - 3515- 3532) |
| 3563 | Total Depth | | |