

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

HOBBS OFFICE O. C. C.

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LE-032450(A)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL x 198' FWL, Sec. 15. (Unit N, SE 1/4 SW 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3276' D. F.

7. UNIT AGREEMENT NAME

SOUTH MATTHEW UNIT

8. FARM OR LEASE NAME

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

FOWLER BLINERY

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

15-24-37 NM PM

12. COUNTY OR PARISH

13. STATE
LEA NEW MEXICO

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sonces pertinent to this work.)*

Abandoned Fowler Blinbury zone by setting a bridge plug at 9835' and squeezing below with 150 sq. (Left 50 sq cement above bridge plug.)

Cemented behind oil string casing and across Blinbury zone as follows: Perforated 5758-60 w/2SPF and squeezed w/ 150 sq. Perforated 5407-09 w/2SPF and squeezed w/175 sq. 2000 and drilled out to 5750.

Perforated Blinbury zone intervals 5409-11, 13-15, 55-56, 60-61, 67-68, 72-74, 94-95, 97-98, 5515-18, 55-56, 80-81, 87-88, 94-95, 5609-10, 16-17, 20-21, 33-34, 55-57, 72-73, 84-85, 5699-5700, 07-08, w/2JSPF. Acidized w/ 2000 gal LSTNE.

On PT. Flowed 18760 + 2 BW in 24 hours thru 2 9/16" Choke. TPF 480. GOR 480. Cgr. 39.5%. 186 MCF

OC - 1-10-66
Comp - 1-24-66

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

Area Sup

1-24-66

04. USGS- (This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

1-GRANTIC REC. 15
1-CONOCO
1-STD OF TEX
1-TENNESSEE
1-STATE LAND

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

JAN 24 1966