

Form 9-311
(Feb. 1951)

DUPLICATE

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces

Lease No. 032450-(a)

Unit South Mattix Unit

APPROVED

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

South Mattix Unit #6

Hobbs, New Mexico, September 26, 1951

Well No. 6 is located 1980 ft. from N line and 660 ft. from E line of sec. 15

N 1/4 24-6 37-8 NMP
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Fowler Las New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3240 ft. est.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill an Allenburger test well with rotary tools to approximately 10,500'.

Casing program is as follows:

13-3/8" @ 300' cemented with 380 sacks neat, circulated to surface.

9-5/8" @ 3650' cemented in two stages: 1st stage, 375 sacks of 8% gel, plus 100 sacks neat.

2nd stage, 150 sacks neat.
staging collar to be set at top of salt section, approx. 1100'.

7" @ 10,500' cemented in two stages: 1st stage 400 sacks 8% gel plus 125 sacks neat.

2nd stage 300 sacks 8% gel plus 50 sacks neat.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

(See reverse)

Company Stanolind Oil and Gas Company

Address Box F

Hobbs

New Mexico

By Ralph J. Vennema

Title Field Superintendent

ORIGINAL
RECEIVED

Copies of electric logs, sample logs, temperature
and other surveys will be submitted to your office
upon completion of the well.

Copies of location plat are attached.

Sealing collar to be set at
approximately 1000'.