


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces

Lease No. 032450(1)

Unit South Mattix Unit



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 23, 1952

Well No. 7 is located 660 ft. from N line and 660 ft. from W line of sec. 15

NW/4 Sec. 15
(1/4 Sec. and Sec. No.)

24-S
(Twp.)

37-E
(Range)

NMPM
(Meridian)

Fowler
(Field)

Lea
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill subject well to approximately 10,500 with Rotary Tools, using the following casing and cementing program:

Casing Size	Hole Size	Depth	Cement
13-3/8"	17-1/2"	300	Circulated to surface
9-5/8"	12-1/4"	3650	*1st Stage 375 sx 8 1/2 gel plus 100 sx Reg. 2nd Stage 150 sx neat
7"	8-3/4"	10,500	Single Stage - 900 sx plus 4 1/2 gel plus 900 cu ft Perlite.

*Staging collar to set at top of salt.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Stanolind Oil and Gas Co.

Address Box 68

Hobbs, New Mexico

By K. A. Henderson

Title Field Superintendent